

SCALANCE XB008G unmanaged Industrial Ethernet Switch for 10/100/1000 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V DC power supply, with 8x 10/100/1000 Mbit/s RJ45 ports electrical Manual available as a download



Product type designation	SCALANCE XB008G
Transmission rate	
Transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
Interfaces / for communication / integrated	
Number of electrical connections • for network components or terminal equipment	8; RJ45
Number of 100 Mbit/s SC ports • for multimode	0
Interfaces / others	
Number of electrical connections • for power supply	1
Type of electrical connection • for power supply	3-pole terminal block
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage • external	24 V

• external / minimum	19.2 V
• external / maximum	28.8 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.52 A
Power loss [W]	
• at DC / at 24 V	12.5 W

Permitted ambient conditions

Ambient temperature	
• during operation	-10 ... +60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Design	Box
Width	45 mm
Height	100 mm
Depth	87 mm
Net weight	0.26 kg
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
• S7-1500 rail mounting	No

Product functions / management, configuration

Product function	
• multiport mirroring	No
• CoS	Yes
PROFINET conformity class	A
Product function / switch-managed	No

Product functions / Redundancy

Product function	
• Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No

Standards, specifications, approvals

Standard	
----------	--

- for FM
- for hazardous zone
- for safety / from CSA and UL
- for emitted interference
- for interference immunity

FM3611: Class 1, Division 2, Group A, B, C, D / T4, CL.1, Zone 2, GP, IIC, T4
 EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
 UL 60950-1, CSA C22.2 No. 60950-1
 EN 61000-6-4 (Class B)
 EN 61000-6-2

Standards, specifications, approvals / CE

Certificate of suitability / CE marking	Yes
---	-----

Standards, specifications, approvals / miscellaneous

Certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes
• KC approval	Yes

Standards, specifications, approvals / product conformity

MTBF	112 y
------	-------

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
----------------------	--

last modified:

10/15/2019