Eaton 9PXMSPPM

Catalog Number: 9PXMSPPM

Eaton 9PXM 4 kVA / 3.6 kW split-phase power module

General specifications

Product Name	Catalog Number
Eaton 9PXM split-phase power module	9PXMSPPM
UPC	Product Length/Depth
OFC	Floduci Lengin/Depin
743172091437	8.5 in
Product Height	Product Width
23 in	6 in
Product Weight	Compliances
22.5 lb	TAA Compliant
	FCC Compliant



Certifications

IEC Rated cULus Listed

Battery

Runtime graph

View runtime graph

Battery replacement

Hot-swappable internal batteries and extended battery modules (EBMs)

Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

Extended battery capability

Yes

Environmental

Temperature range 0° to 40°C (32° to 104°F)

Relative humidity 5-95% non-condensing

Electrical input

Input connection

Hardwired

Input nominal voltage 110V/220V, 120V/208V, 120V/240V, 127V/220V

Input power factor

>0.99 typical

Input frequency range 60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz

Electrical output

Output frequency 60 Hz

Voltage

120/208V

Output nominal voltage 110V/220V, 120V/208V, 120V/240V, 127V/220V

Output waveform

True sine wave

Output power factor

0.9

Topology Online/Double-conversion

Additional specifications

Package contents 9PXMSPPM power module Internal bypass

Yes Color

Black/silver

Hot swap power

Yes

Resources

Drawings

Eaton 9PXM super charger and power module drawing

Specifications and datasheets

Eaton Specification Sheet - 9PXMSPPM



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2023 Eaton. All Righ Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2023 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia