

PRODUCT-DETAILS

GAF2050-10-11-70

GAF2050-10-11 100-250V 50/60Hz/DC

Contactor



General Information

Extended Product Type	GAF2050-10-11-70
Product ID	1SFL707025R7011
EAN	7320500408254
Catalog Description	GAF2050-10-11 100-250V 50/60Hz/DC Contactor
Long Description	A 3-pole Contactor suitable for DC-1 applications where all three poles must be connected in series in a 1-pole configuration up to max 1000 VDC. Operated with wide control voltage range 100-250 V, AC/DC

Classifications

Object Classification Code	Q
ETIM 4	EC002552 - Power contactor, DC switching
ETIM 5	EC002552 - Power contactor, DC switching
ETIM 6	EC002552 - Power contactor, DC switching
ETIM 7	EC002552 - Power contactor, DC switching
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4755 >> Contactors

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	555 mm
Package Level 1 Depth / Length	365 mm
Package Level 1 Height	500 mm
Package Level 1 Gross Weight	35 kg
Package Level 1 EAN	7320500408254

Certificates and Declarations (Document Number)

CB Certificate	SEMKO_SE-76673
CCC Certificate	CQC_2012010304550984
cUL Certificate	9AKK107046A9917
Declaration of Conformity - CE	2CMT003517
EAC Certificate	9AKK107046A8618
Environmental Information	1SFC101066D0201
Instructions and Manuals	1SFC101047M9701
RoHS Information	2CMT003517
UL Listing Card	UL_E73397

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(1000 V DC) 2050 A (440 V DC) 2050 A (600 V DC) 2050 A

Environmental

Ambient Air Temperature	Operation -40 ... +70 °C Storage -40 ... +70 °C
Maximum Operating Altitude Permissible	3000 m
RoHS Status	Following EU Directive 2011/65/EU

Technical

Number of Main Contacts NO	1
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Main Circuit 1000 V
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 2050 A

Rated Operational Current DC-1 (I_e)	(1000 V) 3 Poles in Series, 40 °C 2050 A (1000 V) 3 Poles in Series, 55 °C 1750 A (1000 V) 3 Poles in Series, 70 °C 1500 A (220 V) 3 Poles in Series, 40 °C 2050 A (220 V) 3 Poles in Series, 55 °C 1750 A (220 V) 3 Poles in Series, 70 °C 1500 A (400 V) 3 Poles in Series, 40 °C 2050 A (400 V) 3 Poles in Series, 55 °C 1750 A (400 V) 3 Poles in Series, 70 °C 1500 A (600 V) 3 Poles in Series, 40 °C 2050 A (600 V) 3 Poles in Series, 55 °C 1750 A (600 V) 3 Poles in Series, 70 °C 1500 A
Rated Insulation Voltage (U_i)	acc. to UL/CSA 1000 V
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Mechanical Durability	0.5 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)
Rated Control Circuit Voltage (U_c)	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 48 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 48 V·A Holding at Max. Rated Control Circuit Voltage DC 16 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 1900 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 1900 V·A Pull-in at Max. Rated Control Circuit Voltage DC 1700 V·A
Connecting Capacity Main Circuit	Bar 100 mm
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 Flexible with Insulated Ferrule 1x 0.75 ... 2.5 Flexible 2x0.75 ... 2.5 m² Solid 2 x 1 ... 4 m² Stranded 2 x 1 4 m²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type	Main Circuit: Bars

Dimensions

Product Net Width	438 mm
Product Net Depth / Length	244 mm
Product Net Height	392 mm
Product Net Weight	33 kg

Popular Downloads

Data Sheet, Technical Information	1SBC100192C0206
Instructions and Manuals	1SFC101047M9701
Dimension Diagram	53540930-7

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

