

Molded Case Circuit Breakers

Q-Line Circuit Breakers

Bolt-on Circuit Breakers
240V Class

TQB, THQB 120/240 Vac

| # of Poles | Ampere Rating | Wire Range ¹ | 120/240 Vac Interrupting Rating | Product Number |
|------------|---------------|-------------------------|---------------------------------|-----------------------|
| 1 | 10 | 14-8 Cu/12-8 Al | 5kA | TQB1110 ³ |
| 1 | 15 | 14-8 Cu/12-8 Al | 10kA | THQB1115 ² |
| 1 | 20 | 14-8 Cu/12-8 Al | 10kA | THQB1120 ² |
| 1 | 25 | 14-8 Cu/12-8 Al | 10kA | THQB1125 |
| 1 | 30 | 14-8 Cu/12-8 Al | 10kA | THQB1130 |
| 1 | 35 | 8-3 Cu/8-3 Al | 10kA | THQB1135 |
| 1 | 40 | 8-3 Cu/8-3 Al | 10kA | THQB1140 |
| 1 | 45 | 8-3 Cu/8-3 Al | 10kA | THQB1145 |
| 1 | 50 | 8-3 Cu/8-3 Al | 10kA | THQB1150 |
| 1 | 60 | 8-3 Cu/8-3 Al | 10kA | THQB1160 |
| 1 | 70 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB1170 |



THQB2115

TQB, THQB 120/240 Vac, Internal Common Trip

| # of Poles | Ampere Rating | Wire Range ¹ | 120/240 Vac Interrupting Rating | Product Number |
|------------|---------------|-------------------------|---------------------------------|----------------------|
| 2 | 10 | 14-8 Cu/12-8 Al | 5kA | TQB2110 ³ |
| 2 | 15 | 14-8 Cu/12-8 Al | 10kA | THQB2115 |
| 2 | 20 | 14-8 Cu/12-8 Al | 10kA | THQB2120 |
| 2 | 25 | 14-8 Cu/12-8 Al | 10kA | THQB2125 |
| 2 | 30 | 14-8 Cu/12-8 Al | 10kA | THQB2130 |
| 2 | 35 | 8-3 Cu/8-3 Al | 10kA | THQB2135 |
| 2 | 40 | 8-3 Cu/8-3 Al | 10kA | THQB2140 |
| 2 | 45 | 8-3 Cu/8-3 Al | 10kA | THQB2145 |
| 2 | 50 | 8-3 Cu/8-3 Al | 10kA | THQB2150 |
| 2 | 60 | 8-3 Cu/8-3 Al | 10kA | THQB2160 |
| 2 | 70 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB2170 |
| 2 | 80 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB2180 |
| 2 | 90 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB2190 |
| 2 | 100 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB21100 |

TQB, THQB 240 Vac, Internal Common Trip

| # of Poles | Ampere Rating | Wire Range ¹ | 240 Vac Interrupting Rating | Product Number |
|------------|---------------|-------------------------|-----------------------------|-----------------------|
| 2 | 10 | 14-8 Cu/12-8 Al | 5kA | TQB22010 ³ |
| 2 | 15 | 14-8 Cu/12-8 Al | 10kA | THQB22015 |
| 2 | 20 | 14-8 Cu/12-8 Al | 10kA | THQB22020 |
| 2 | 25 | 14-8 Cu/12-8 Al | 10kA | THQB22025 |
| 2 | 30 | 14-8 Cu/12-8 Al | 10kA | THQB22030 |
| 2 | 35 | 8-3 Cu/8-3 Al | 10kA | THQB22035 |
| 2 | 40 | 8-3 Cu/8-3 Al | 10kA | THQB22040 |
| 2 | 45 | 8-3 Cu/8-3 Al | 10kA | THQB22045 |
| 2 | 50 | 8-3 Cu/8-3 Al | 10kA | THQB22050 |
| 2 | 60 | 8-3 Cu/8-3 Al | 10kA | THQB22060 |
| 2 | 70 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB22070 |
| 2 | 80 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB22080 |
| 2 | 90 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB22090 |
| 2 | 100 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB22100 |
| 3 | 10 | 14-8 Cu/12-8 Al | 5kA | TQB32010 ³ |
| 3 | 15 | 14-8 Cu/12-8 Al | 10kA | THQB32015 |
| 3 | 20 | 14-8 Cu/12-8 Al | 10kA | THQB32020 |
| 3 | 25 | 14-8 Cu/12-8 Al | 10kA | THQB32025 |
| 3 | 30 | 14-8 Cu/12-8 Al | 10kA | THQB32030 |
| 3 | 35 | 8-3 Cu/8-3 Al | 10kA | THQB32035 |
| 3 | 40 | 8-3 Cu/8-3 Al | 10kA | THQB32040 |
| 3 | 45 | 8-3 Cu/8-3 Al | 10kA | THQB32045 |
| 3 | 50 | 8-3 Cu/8-3 Al | 10kA | THQB32050 |
| 3 | 60 | 8-3 Cu/8-3 Al | 10kA | THQB32060 |
| 3 | 70 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB32070 |
| 3 | 80 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB32080 |
| 3 | 90 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB32090 |
| 3 | 100 | 6-1/0 Cu/4-1/0 Al | 10kA | THQB32100 |

¹Solid or stranded for 14-10 AWG.

²UL listed as SWD (Switching Duty) rated. Suitable for switching 120 Vac fluorescent lighting loads.

³Not UL listed.

UL listed HACR (heating, air conditioning and refrigeration).