



Representative Image

Catalog No. THQB2115

Description: ASM THQB C/B 2 POLE 120/240V

UPC No 783164012231

Q line circuit breakers are one-inch wide per pole, compact, thermal-magnetic devices designed for residential and commercial applications. The QB breakers are bolt-on versions of the Q Line used for bolting to the bus connections of load centers and lighting panels. All Q Line circuit breakers feature Quick-make / Quick-break mechanisms, common trip bars, and easy to spot trip indication to ensure safety and reliability. Q Line breakers are available in 1, 2, and 3 pole versions, can be ordered with auxiliary contact and shunt trip accessories, and can be ordered for use in HID applications. 2115 Amps 15 A 21152231

Descriptors	
Category	Mini Circuit Breakers & Supplementary Protectors
Product Line	TEY / Q-Line (Bolt-On)
GO Schedule	EB

Specifications		
Trip Style	Non-Interchangeable	
Frame Type	Q-Line	
Amperage	15 A	
System Voltage	120 Vac, 120/240 Vac	
Poles	2	
Trip Function	LI	
Continuous Current Rated	Standard	
120 Vac Interrupting Rating	10 KAIC	
120/240 Vac Interrupting Rating	10 KAIC	
Suitable for Reverse Feed	Yes	
Wire Range (Cu/Al)	14-8 kcmil / 12-8 kcmil	
Long Time	Fixed	
Instantaneous	Fixed	
Protective Relays	No	
Current Metering	No	
Special Markings	HACR	
GSA Compliance	Yes	

Classifications	
UL File #	E11592

geindustrial.com Created on: 05/11/2019

Publications				
Title	Publication No.	Publication Type		
Q-Line Bolt-On MCCB, 100A Frame 1-, 2-, or 3- Pole, Drawing	455C873-SH1	Drawings-Outline and Dimensional		
1-Page fully dimensioned outline drawing in .pdf format				

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.

geindustrial.com Created on: 05/11/2019