

# Mounting Bases, Cable Ties and Accessories

Installs in-line with the wire bundle!

### **In-Line Mounting Base**





BULK Cat. No.	MOUNTING METHOD	WIDTH ACCOM. IN./MM	Max. Tie Width In./Mm	LENGTH IN./MM	BULK PKG. QTY.
TC815-TB	#10 screws	.30/7.62	.75/19.05	1.13/28.58	500
• Natural nyl	on color.	installs in-line with th ing from -40° F to 1			

### **Miniature Base**





BULK PKG. Cat. No.	MOUNTING Method	MAX. TIE WIDTH ACCOM.	LENGTH IN./MM	WIDTH IN./MM	MATERIAL	BULK PKG. QTY.	
TC817-TB	TC2PA	.19	.44/11.10	.44/11.10	Nylon 6/6	1,000	
<ul> <li>Natural nylon color.</li> <li>For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).</li> </ul>							

# Handles ties installed in either direction!

### Low-Profile Four-Way Mounting Base



							713
STD. PKG. CAT. NO.	BULK PKG. Cat. No.	Mounting Method	Maximum Tie Width Accom.	WIDTH IN./MM	LENGTH IN.	STD. PKG.	BULK PKG.
_	TC826-TB*	#8 screw	.19	.50/12.70	1/25.40	_	1,000
TC5828	TC828-TB*	#8 screw	.19	.39/9.91	.88/22.23	100	1,000
or perpend The TC828	icular to lengtl	n of base. plate also har	used to tie bui ndles ties insta				

\*Natural nylon color is standard. Replace TB with O suffix for black color.

For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).

Firmly locks into position when projecting pin is pushed into the mounting hole.

## **Self-Riveting Base**





						- 91
BULK PKG. Cat. No.	MOUNTING Hole PKG. Size	MAX. TIE WIDTH ACCOM.	WIDTH IN./MM	LENGTH IN./MM	MATERIAL	BULK PKG. QTY.
TC116-TB	.146	.190	.5/12.7	.75/19.05	Nylon 6.6 (Red)	1,000
TC116-0	.146	.190	.5/12.7	.75/19.05	Nylon 6.6 (Black)	1,000
TC118-TB	.169	.190	.5/12.7	.75/19.05	Nylon 6.6 (Blue)	1,000
TC120	.196	.190	.5/12.7	.75/19.05	Nylon 6.6 (Yellow)	1,000
Slip tie unde	er base to attac	ch bundle.				

For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).



United States Tel: 901.252.8000 800.816.7809 Fax: 901.252.1354 Technical Services Tel: 888.862.3289

