

10464 Series watertight fittings for ACWU cable



| Cat. no. | Hub size (in.) | Cable jacket O.D. (in.) | | Throat dia. (in.) |
|----------|----------------|-------------------------|-------|-------------------|
| | | Min. | Max. | |
| 10462* | ½ | 0.562 | 0.625 | 0.615 |
| 10464 | ½ | 0.625 | 0.760 | 0.615 |
| 10465-TB | ½ | 0.750 | 0.885 | 0.615 |
| 10466 | ½ | 0.875 | 0.985 | 0.615 |
| 10467 | ¾ | 0.880 | 1.065 | 0.780 |
| 10468 | ¾ | 1.055 | 1.205 | 0.780 |
| 10469 | 1 | 1.187 | 1.375 | 1.000 |
| 10470 | 1¼ | 1.375 | 1.625 | 1.187 |
| 10550 | 1¼ | 1.375 | 1.625 | 1.400 |
| 10471 | 1¼ | 1.625 | 1.875 | 1.400 |
| 10472 | 1½ | 1.750 | 1.965 | 1.563 |
| 10473 | 1½ | 1.937 | 2.187 | 1.621 |
| 10551 | 2 | 2.000 | 2.187 | 2.000 |
| 10474 | 2 | 2.156 | 2.360 | 2.000 |
| 10475 | 2 | 2.350 | 2.565 | 2.000 |
| 10552 | 2 | 2.350 | 2.565 | 2.092 |
| 10476 | 2 | 2.535 | 2.750 | 2.092 |
| 10553 | 2½ | 2.535 | 2.750 | 2.437 |
| 10477 | 2½ | 2.735 | 2.985 | 2.437 |
| 10478 | 2½ | 2.970 | 3.220 | 2.437 |
| 10554 | 3 | 2.975 | 3.125 | 3.050 |
| 10555 | 3 | 3.080 | 3.250 | 3.050 |
| 10479 | 3 | 3.210 | 3.380 | 3.050 |
| 10480 | 3 | 3.310 | 3.480 | 3.050 |
| 10481 | 3½ | 3.430 | 3.620 | 3.310 |
| 10482 | 3½ | 3.560 | 3.750 | 3.310 |
| 10483 | 3½ | 3.710 | 3.870 | 3.310 |
| 10484 | 4 | 3.810 | 4.000 | 3.560 |
| 10485 | 4 | 3.930 | 4.120 | 3.670 |
| 10486 | 4 | 4.060 | 4.250 | 3.800 |

Note - When using fittings on single-conductor cable, aluminum fittings and aluminum locknuts must be used.

*Cat. no. 10462 not UL Listed

Materials

- Malleable iron: The above listed catalogue numbers relate to malleable iron fittings with a protective grounding sleeve for jacketed metal-clad cable.
- Aluminum: Available up to 21/2 inches. To order add suffix "AL" to the catalogue number (example 10478AL).
- PVC-coated aluminum and steel: Contact your regional sales office for availability and ordering information.

Certifications

- Type HLA. CSA certified Classes I, II and III. These fittings are suitable for Class I hazardous locations when used in combination with a certified Class I hazardous location sealing fitting.
- Type OLA. UL listed. These fittings are suitable for use interlocked jacketed cable, aluminum or steel armour.