

Hazardous location fittings

GUA conduit outlet boxes – Now available in stainless steel 316

Application

GUA boxes can be used for hazardous location conduit runs for the following:

- Allows for mounting of fixture outlets (when used with appropriate covers)
- Provides easy access to wiring
- Provides junction in conduit for wire pulling and splices
- Changes direction in rigid conduit systems
- Attaches two or more pieces of conduit in long runs
- Guards against damage to wires in rigid conduit

Features

- All hubs have a minimum of five full threads and integral bushing
- All boxes are furnished with internal grounding screw
- Cover supplied with O-ring gasket
- Easier and faster to clean with exceptionally smooth hygienic markings on stainless steel 316 version

Size range

- ½" NPT to 2" NPT
- Access opening 2" to 5" diameter



GUA



Cat. no.	Hub size (in.)	Dimensions (in.)			Throat dia. (in.)		Cu. in. capacity
		A	B	C	Min.	Max.	
GUA14-TB	½	1.81	2.50	0.88	0.570	0.610	5.5
GUA16-TB	½	2.00	3.50	0.88	0.570	0.610	13.5
GUA24-TB	¾	2.00	2.50	0.88	0.755	0.810	5.3
GUA26-TB	¾	2.00	3.50	0.88	0.755	0.810	13.3
GUA36-TB	1	2.31	3.50	0.88	0.935	1.035	16.2
GUA47-TB	1¼	2.69	4.38	1.00	1.260	1.360	29
GUA59-TB	1½	3.81	5.75	1.06	1.470	1.590	70

Materials

- Bodies: grade 60-45-10 ductile iron (complies with ASTM standard A536)
- Covers: die-cast aluminum
- Options: Stainless steel 316 body and cover – replace “-TB” with “- SST”*

Finish

- Boxes: zinc-plated with aluminum acrylic paint
- Covers: natural
- Stainless steel 316: polished

Listings/compliances

- UL514A (wet locations when used with gasketed covers)
- UL 1203
- CSA: C22.2 No. 30
- Cl. I, Div. 1 & 2, Groups C, D, Cl. II, Div. 1, Groups E, F, G, Cl. III, Div. 1 & 2
- NEMA 3, 4, 7 CD, 9 EFG
- Explosion-proof
- Dust-ignition-proof
- Raintight
- Wet locations
- cULus (stainless steel 316)



Stainless steel version coming soon

GUAB



Cat. no.	Hub size (in.)	Dimensions (in.)			Throat dia. (in.)		Cu. in. capacity
		A	B	C	Min.	Max.	
GUAB14-TB	½	2.25	2.50	0.88	0.570	0.610	6.9
GUAB16-TB	½	2.00	3.50	0.88	0.570	0.610	13.5
GUAB24-TB	¾	2.50	2.50	0.88	0.755	0.810	7.9
GUAB26-TB*	¾	2.00	3.50	0.88	0.755	0.810	13.5
GUAB36-TB*	1	2.31	3.50	1.00	0.935	1.035	15.4
GUAB47-TB	1¼	2.69	4.38	1.00	1.260	1.360	27.5
GUAB59-TB	1½	3.81	5.75	1.06	1.470	1.590	73.6
GUAB69-TB	2	4.06	5.75	1.06	1.880	2.047	80
GUAB79-TB	2½	4.06	5.75	1.13	2.320	2.380	98

*Available in stainless steel 316, cULus listed.

Diagrams

