

Flexible Fixture Hangers

Receptacle and Hook and Loop

UNILETS® for Use with Threaded Rigid Metal Conduit and IMC.

Applications

- Designed for suspension of HID, fluorescent and incandescent lighting fixtures.

Features

- Permit quick disconnect and removal of fixture for maintenance.
- Available in pendant or feed-thru.
- Available with matching cord set.

Standard Materials

- Malleable iron with steel cover
- Screws: stainless steel

Standard Finishes

- Malleable iron parts: triple-coat—(1) zinc electroplate, (2) chromate, and (3) epoxy powder coat
- Steel parts: zinc electroplate



GHPHP



GHPHT

GHPHP and GHPHT — Receptacle Hangers

		Conduit Hub Size (Inches)	Voltage	Hubbell Plug	Catalog Number	
					Pendant	Feed-Thru
Furnished with assembled FS box, EFHM, safety lock, receptacle, and steel cover. Supports 200 lbs/ 90.7kg.						
		3/4	120	L5-15P	GHPHP12	GHPHT12
		3/4	208, 240	L6-15P	GHPHP24	GHPHT24
		3/4	277	L7-15P	GHPHP27	GHPHT27
		3/4	347	L37-20P	GHPHP34	GHPHT34
		3/4	480	L8-20P	GHPHP48	GHPHT48
		3/4	600	L9-20P	GHPHP60	GHPHT60
GHPHP	GHPHT					

Cord Sets — With Loop — Supplied with 600 V, 90°C 3 conductor No. 16 SOW cable, locking plug and 3/4" FHLM loop

		Voltage	Amperes	2'/0.6 m Cord	3'/0.9 m Cord	4'/1.21 m Cord
		120	15	G-HCPL-2-12	G-HCPL-3-12	G-HCPL-4-12
		208, 240	15	G-HCPL-2-24	G-HCPL-3-24	G-HCPL-4-24
		277	15	G-HCPL-2-27	G-HCPL-3-27	G-HCPL-4-27
		347	20	G-HCPL-2-34	G-HCPL-3-34	G-HCPL-4-34
		480	20	G-HCPL-2-48	G-HCPL-3-48	G-HCPL-4-48
		600	20	G-HCPL-2-60	G-HCPL-3-60	G-HCPL-4-60

CSA Approved.