

OF TO

Actual

Catalog Number: 260-1050

 Product ID:
 7TCA296230R0060

 EAN Number:
 05016947002354

Status: Active

Cable Gland, Stripped Cable Sheath Allowing the Outer Sheath to Be Completeley Stripped from the Cable, M16 Thread, 10mm Thread Length, 26.7mm Gland Diameter, 24mm Across Flats Diameter, 6-9mm Cable Diameter Range, Nickel Plated Brass, Stainless Steel Spring, Rubber Seal, IP68

North American Specifi	cations (UNSPSC)
UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	Adaptaflex
Туре	Index EMC Type A Cable Gland
Special Features	Stripped Cable Sheath - Allowing the Outer Sheath
	to Be Completeley Stripped from the Cable
Application	Provide Strain Relief and Connection for Conduit
	Systems
Size	M16
Conductor Range	6.0 to 9.0mm
Material	Nickel Plated Brass, Stainless Steel Spring, Rubber
	Seal (TPE-V)
Color	Brass
Insulation	IP68
Temperature Rating	-40 Degrees C to +135 Degrees C

European Specifications (ETIM)		
ETIM	EC000441 Cable screw gland	
Thread type	Metric	
Nominal thread size metric/PG	16	
Thread length	10mm	
Wrench width	24mm	
Hexagon angular dimension	26.7mm	
Suitable for cable diameter	6-9mm	
Material	Metal	
Material quality	Brass	
Surface protection	Nickel-plated	
Halogen free	Υ	
Glass-fibre reinforced	N	
Degree of protection (IP)	IP68	
Shock resistant	N	
Colour	Other	
Bend radius protection/trumpet flare	N	
With locknut	N	
Model	Straight	
Flat cable coupling	N	
Strain relief	N	
Operating temperature	-40-+135°C	
Explosion-tested version	N	
For Ex-zone gas	None	
For Ex-Zone dust	None	
EMC-version	Υ	

Packaging	
Outer Quantity	250
Outer Dimensions (inches)	14x14x6
Weight Uom	0.21 lbs. Each



For further technical assistance, please contact us...

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com