



Actual

Catalog Number: **SPL25/25M**
Product ID: 7TCA296030R0193
EAN Number: 05020963000263
Status: Active

Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Black

- Very high UV resistance
- Medium flexibility
- Medium fatigue life
- Self Extinguishing

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Adaptaflex
Type	Oil Resistant Conduit
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Trade Size	3/4 Inch/NC 25mm
Outside Diameter	26.4mm
Inside Diameter	21.0mm
Length	25 Meters
Radius	110mm
Flexibility	Medium
Material	Galvanized Steel Core with PVC Covering
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	25mm
Outer diameter	26.4mm
Inner diameter	21mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	PVC
Operating temperature	-20-+105°C
Degree of protection (IP)	IP68
Weight	0.353kg/m
Colour	Black
Bending strength	Flexible
With approval according to UL	Y

Packaging

Inner Quantity	1
Outer Quantity	24
Outer Dimensions (inches)	16x17x16
Weight Uom	29.76 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com