

EFD/EFDB Series Factory Sealed Dust Cap Push Button Stations

Explosionproof, Dust-Ignitionproof

10 Amp, 600 Vac Max. for Heavy Duty Use. Momentary Contact. Furnished with Internal Ground Screw.

Class I, Division 1, Groups B⁺, C, D
 Class I, Division 2, Groups B, C, D
 Class II, Division 1 and 2, Groups E, F, G
 Class III
 NEMA 3, 7CD, 9EFG

Controls

CONTROLS: HAZARDOUS LOCATION CONTROL STATIONS AND SWITCHES

	Hub Size (Inches)	Description	Nameplate Marking	Catalog Number Dead-End Feed-Thru	
1-Gang *					
	3/4	1 Circuit Universal		Start/Stop	EFDB175-DU1 EFDCB175-DU1
	1				EFDB110-DU1 EFDCB110-DU1
	3/4	2 Circuits Universal		Start/Stop	EFDB175-DU2 EFDCB175-DU2
	1				EFDB110-DU2 EFDCB110-DU2
3-Device †					
	3/4	2 Circuits Universal and 1 Pilot Light		Start/Stop	EFDL75-J1DU2 EFDCL75-J1DU2
	1				EFDL10-J1DU2 EFDCL10-J1DU2

* Malleable iron body and aluminum cover. For aluminum body, add suffix -A.

‡ Aluminum body not available.

◆ Shaded area indicates items suitable for Class I, Groups B, C and D; Class II, Groups E, F, and G; and Class III. For Class I, Group B external seals must be installed at each conduit entrance.