

Materials:

- Low Carbon Steel ($F_y = 32,000$ psi minimum, $F_t = 52,000$ psi minimum)

Finishes:

- **Electrogalvanized (EG):**
Conforms to ASTM B633, Type III SC1
- **Unistrut Defender (DF):**
Conforms to ASTM A1059

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 316 (SS):** ASTM A240, Type 316 *

* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	Thread Size	Length (ft)	Finish	Product Weight / Ft (lbs/ft)
HTHR025	1/4"	10'	EG	0.12
HTHR025	1/4"	12'	EG	0.12
HTHR031	5/16"	10'	EG	0.2
HTHR031	5/16"	12'	EG	0.2
HTHR037	3/8"	10'	EG	0.29
HTHR037	3/8"	12'	EG	0.29
HTHR037	3/8"	6'	DF	0.29
HTHR044	7/16"	10'	EG	0.4
HTHR044	7/16"	12'	EG	0.4
HTHR050	1/2"	10'	EG	0.53
HTHR050	1/2"	12'	EG	0.53
HTHR050	1/2"	6'	DF	0.53
HTHR062	5/8"	12'	EG	0.84
HTHR062	5/8"	10'	EG	0.84
HTHR075	3/4"	12'	EG	1.24
HTHR075	3/4"	10'	EG	1.24
HTHR087	7/8"	10'	EG	1.7
HTHR087	7/8"	12'	EG	1.7
HTHR100	1"	10'	EG	2.23
HTHR100	1"	12'	EG	2.23

Project:

Architect / Engineer:

Date: **Phone:**

Contractor:

Address: