

SLLP23-700P88

LS SERIES TYPE 4 SIMPLE SAFETY LIGHT CURTAINS



EZ-SCREEN LS, Pair

Resolution: 23 mm; Range: 12 m (40 ft)

Defined Area: 700 mm (27.6 in.); Housing: Yellow

Connection: M12 8-pin 300 mm Pigtail QD; 2x

OSSD, EDM, Fault Out & Fault Reset

Part Number: 89695

CERTIFICATIONS





SPECIFICATIONS

Primary Housing Material	Aluminum
Safety Level	Type 4
Effective Aperture Angle	Type 4 Per IEC 61496-2
Connector Type	M12 Pigtail (Yellow)
Defined Area (mm)	700
Dimensions WxD (mm)	36 x 42.5
Overall Length (mm)	704

Fixed Blanking	No
Housing Finish	Yellow Polyester
IP Rating	IP65; IP67
Number of Pins (Receiver/Emitter)	8
Operating Range (m)	0.1 - 12
Operating Voltage	24 V dc +/- 15%
Operating Temperature	-20 to +55 deg. C; RH 95%
PL Rating	Ple
Recovery Time	55 / 186
Reduced Resolution	No
Response Time	13.3
SIL Rating	SIL3; CL3
Electrical Safety Class	III
Scan Code	Selectable
Shock	10g at 16 ms (6000 cycles)
Short Protection	Yes
System Type	Pair
Vibration	10-55 Hz at 0.35 mm
Auxiliary Output	No
Fault Output	Yes
Housing Material	Aluminum; Zinc; Acrylic
OSSD Rating	24 V dc at 0.5 A each
Supply Current	107 mA Typical
Trip/Latch Output	Trip

Feature: End-to-End Sensing	Yes
Feature: ESD Safe	No
Feature: Integral Muting	No
Feature: Compact Housing	No

RELATED PRODUCTS

DOUBLE ENDED CORDSETS

