



T303E

▶ T30 SERIES 60 M RANGE IP69K WASHDOWN RATED SENSOR



EZ-BEAM T30 Series: Emitter

Range: 60 m; Input: 20-250V ac

Output: Not applicable - No outputs

2 m (6.5 ft) cable

Part Number: 32494

CERTIFICATIONS



SPECIFICATIONS

Sensing Mode (General)	Opposed
Sensing Mode (Detailed)	Emitter
Housing Style	Barrel
Primary Housing Material	Thermoplastic
Max Sensing Distance (mm)	60000
Power Supply/Supply Voltage	20-250 V ac
Connection	2 m Cable
Quick Disconnect Type	No QD
Sensing Beam	Infrared LED

Operation	N/A
Max Op. Temp. (°C)	70
Min Op. Temp. (°C)	-40
Output response time (ms)	16 ON/8 OFF
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	100
Repeatability (µs)	2000
Number of Pins	2
NEMA Rating	NEMA 6P
Max Op. Relative Humidity [%]	90% @ 50°C
Adjustments	N/A
Barrel Diameter (mm)	30
Indicator	LEDs
Opposed Mode Emitter/Receiver	Emitter
Feature: Timing (Hold/Delay)	No
Feature: Ecolab Certified	Yes
Feature: Encapsulated	Yes
Feature: Hazardous Area	No
Feature: Audible	No
DeviceNet	No



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America