

**Catalog Number:** ASL 350-48 TN  
**Product ID:** 7TAA262010R0066  
**UPC Number:** 78378669650  
**Status:** Active

Tin-Plated Aluminum Compression Stacking Lug for Aluminum and Copper Terminations, One-Hole NEMA Pad, 350 KCMIL, 1/2 inch Bolt. This part is not for stacking with AL 350-48. 4.275 inch long x 1.555 inch wide pad.

**North American Specifications (UNSPSC)**

UNSPSC	39121448 Wire or cable compression connector
IGCC	4668 Wire or cable compression connector
Brand Name	Blackburn
Type	Stacking Lug
Special Features	Dual rated for use with Aluminum and Copper Conductors. Prefilled with Oxide Inhibitor to prevent oxidation and keep out moisture. All lugs marked with conductor sizes and die references for easy installation.
Application	General Purpose Lugs for Aluminum and Copper Terminations
Standard	ANSI C119.4
Size	4.275 inch long
Conductor Range	350 kcmil
Material	Aluminum
Finish	Tin-Plated
Insulation	No
Bolt Size	1/2 inch

**Packaging**

Outer Quantity	25
Outer Dimensions (inches)	1x1x1
Weight Uom	0.25 lbs. Each

**Documents / Support Tools**

SDS US 1	sds-00041-tb2
----------	---------------

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com