



Representative

**Catalog Number:** PT-79505  
**Product ID:** 7TAA263800R0096  
**UPC Number:** 78378674403  
**Status:** Active

PowerTap Wedges -795 kcmil tap, wire combinations 795-397.5

### North American Specifications (UNSPSC)

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Blackburn
Type	Overhead Wedge Connectors
Special Features	Low Stresses produced at interfaces precludes significant conductor creep and minimize loss of clamping force on connectors. Contact forces are nearly constant during temperature changes or conductor compaction. Driving action helps remove oxidation from conductor and lowers contact resistance. RUS Accepted.
Application	Reliable performance in the harshest of environments.
Connection	Mechanical
Conductor Range	795 kcmil tap, wire combinations 795-397.5
Number Of Conductors	2
Material	Aluminum
Finish	Bare
Insulation	None
Temperature Rating	90 Degrees Celsius
Environmental Conditions	Outdoor Use.

### Packaging

Outer Quantity	10
Outer Dimensions (inches)	1x1x1
Weight Uom	2.28 lbs. Each

### Documents / Support Tools

Technical Drawing / Data Sheet Canada	Available on Website
Safety Data Sheet (SDS) Global	SDS-00042-TB2

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)