

Straight Blade Devices

Residential Grade Plugs, Connectors, Taps and Adapters

Plugs and Connectors



| Device Type | | Straight Plug | | | | Straight Connector | |
|---------------------|-------------------------|--|--|---|---|---|---|
| Rating | Color | Non-Polarized, Two Blade, Spt 1 and 2 Cord 18/2 and 16/2 AWG | Polarized, Two Blade, Spt 1 and 2 Cord 18/2 and 16/2 AWG | Polarized, Two Blade, Light Duty, Wire Range: #16-18 AWG, Up to .25 In. Diameter Cord | Non-Polarized, Two Blade, Heavy Duty, Wire Range: #14-18 AWG, Up to .33 In. Diameter Cord | Polarized, Two Blade, Heavy Duty, Wire Range: #14-18 AWG, Up to .33 In. Diameter Cord | Polarized, Two Blade, Light Duty, Wire Range: #16-18 AWG, Up to .25 In. Diameter Cord |
| NEMA 1-15, 15A 125V | Black Ivory White | — RP123I RP123W | — RP123PI RP123PW | RP101BK — RP101W | RP646 — — | RP648 — — | RP102BK — RP102W |
| | | | | | | | |

Plugs, Taps and Adapters



| Description | Duplex Receptacle, Six Outlets | Single Receptacle, Three Outlets | Single Receptacle, Three Outlets | Two Wire to U-Ground | Cube Tap, without Ground | Male end: 10A 250V, 15A 125V, Locking Female end: 15A 125V, Straight Blade | Male end: 15A 125V, Straight Blade Female end: 10A 250V, 15A 125V, Locking |
|-------------|--------------------------------|----------------------------------|----------------------------------|----------------------|--------------------------|---|---|
| Rating | NEMA 5-15, 15A 125V | | | | | | |
| Ivory | RT600I | RT300I | — | RT200 | — | — | — |
| White | RT600W | RT300W | — | — | RT100W | 9053AB* | 9054AB*† |
| Orange | — | — | RT303 | — | — | — | — |

Note: Adapters are not intended to be used as a replacement for permanent devices. They are intended for temporary use only.

*Not UL Listed.

†Must always be used with grounded receptacle.

Product Dimensions Inches (mm)

| | RP123 | RP101 | RP102 | RP646/RP648 | RP649 |
|---|--------------|--------------|--------------|--------------|--------------|
| A | 1.41" (35.8) | 1.73" (43.9) | 2.19" (55.6) | 2.00" (50.8) | 2.67" (67.8) |
| B | 1.25" (31.8) | 1.25" (31.8) | 1.25" (31.8) | 1.50" (38.1) | 1.49" (37.8) |
| C | 0.89" (22.6) | 0.89" (22.6) | 0.83" (21.2) | 1.60" (40.6) | 1.60" (40.6) |
| D | — | — | — | 0.71" (17.9) | 0.73" (18.5) |

