

Eaton BC50

Catalog Number: BC50

Fuse-link, low voltage, 50 A, AC 500 V, DC 250 V, BS88, 21 x 114 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	BC50
	UPC
	051712844468
EAN	Product Length/Depth
5027590492126	113 mm
Product Height	Product Width
21 mm	21 mm
Product Weight	Warranty
58.5 g	Not Applicable
Compliances	Certifications
CE Marked	IEC 60269-2
RoHS Compliant	BS88

Type

Fuse

Application

general industrial applications

Amperage Rating

50 A

Fitted with:

Centre bolted tags

Current type

AC/DC

Mounting dimension

M10

Center-to-center distance of connections

97 mm

Breaking capacity

80 kA

Rated voltage AC

500 V

Rated voltage DC

250 V

Class

Class gG/gL

Fuse type

BC

Utilization category

gG (cable protection/equipment protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

None

Watt losses

4.9 W

Connection**Catalogs**

CA134002EN

[Bussmann series complete full line catalog no. 1007](#)**Compliance information**[CE AC*, BC*, AD*, BD* fuse-links](#)[UKCA AC*, BC*, AD*, BD* fuse-links](#)**Multimedia**[Eaton Bussmann - Red Spot fuse links](#)**Technical data sheets**[4113 BC fuses](#)

97 mm fixing centre

Construction

BS88

Construction size

Other

Fuse shape

Center bolted tags

Voltage type

AC/DC

Packaging type

Standard

Voltage rating

500 V

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia