# Eaton C14G50

# Catalog Number: C14G50

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 400 Volts AC, 50 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder

## General specifications



Eaton Bussmann series low voltage

cylindrical fuse

Catalog Number

C14G50

UPC

051712754422

Product Length/Depth

EAN

5027590494120

**Product Height** 

14.3 mm

**Product Weight** 

20.6 g

Product Width

14.3 mm

51 mm

Warranty

1 year limited

Certifications

IEC 60269

Compliances

CE Marked GoST-R

RoHS Compliant



## defaultTaxonomyAttributeLabel

# Type fuse Application for industrial applications for general purpose use Amperage Rating 50 A Fuse size 14 x 51 mm Current type AC Breaking capacity 120 kA Frequency rating - max 62 Hz Frequency rating - min 45 Hz Rated voltage AC 400 V Class Class C gL/gG Fuse type C14G Utilization category gG (cable protection/equipment protection) Fuse indicator Other Watt losses 4.8 W Connection Ferrule end x ferrule end

Construction size 14 mm x 51 mm

Fuse shape

## Resources

#### Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-enus.pdf

#### CA134002EN

Bussmann series complete full line catalog no. 1007

#### Compliance information

CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

#### Technical data sheets

720115 Cylindrical fuses

#### Cylindrical

Voltage type

AC

Suitable for

CH14 Modular fuse holder

Material

Ceramic

Mounting method

14 x 51 mm CH Modular fuse holder

Release characteristic

Other

Quantity

10

Voltage rating

400 V



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.

