

Eaton FWX-5A14F

Catalog Number: FWX-5A14F

Eaton Bussmann series FWX high speed fuse, 600V, 5A, 200 kAIC Vac, 50 kAIC at 250 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWX-5A14F
	UPC
	051712795548
EAN	Product Length/Depth
5027590501439	55 mm
Product Height	Product Width
32 mm	73 mm
Product Weight	Warranty
21.2 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	UL Recognized

Product specifications

Fuse indicator

Non Indicating

Interrupt rating

200 kAIC

Construction size

14 mm x 51 mm

Clearing (I2T)

13 at 250 V

Connection

Ferrule end x ferrule end

Material

Ceramic

Release characteristic

Other

Amperage Rating

50 A

Frequency rating - max

62 Hz

Utilization category

aR (accompanied semiconductor protection)

Watt losses

1.3 W

Fuse type

FWX-A14F

Accessories

CH14 Modular fuse holder

FW14-PCB

Type

High speed fuse

Fuse shape

Cylindrical

Breaking capacity

200 kA

Fuse size

14 x 51 mm

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Technical data sheets

720006 FWX

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I2T)

1.6

Voltage rating

690 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)