

TPL

Specifications

Description: DC power distribution fuses for use with Telepower 15100, 15200, TP158HC and TPHCS disconnect systems. For replacement of Bussmann series UBO fuses a TPL-TA adapter kit is necessary.

Dimensions: See dimensions illustrations.

Ratings:

Volts: — 170Vdc
 Amps: — 70-800A
 IR: — 100kA

Agency information: CE, UL Recognized Guide JFHR2, File E56412 Bellcore.

Features and benefits

- Current-limiting capability designed for DC power distribution systems
- Recognized branch circuit protection
- Complete system coordination capability
- Energy savings with low watts loss, low operating temperatures, and minimum I²t levels

Typical applications

- Telecommunications power circuit protection

Catalog numbers


Catalog numbers	Amp rating
TPL-BA	70
TPL-BB	80
TPL-BC	90
TPL-BD	100
TPL-BE	125
TPL-BF	150
TPL-BG	175
TPL-BH	200
TPL-BK	225
TPL-BL	250
TPL-CN	300
TPL-CO	350
TPL-CR	400
TPL-CU	450
TPL-CV	500
TPL-CZ	600
TPL-CZH	800

Accessories


- Spare fuse holders: TPSFH-LB (for TPL-B fuses)
 TPSFH-LC (for TPL-C fuses)



Dimensions - in (mm)



TPL-BA, TPL-BD, TPL-BF, TPL-BH, TPL-BK, and TPL-BL



TPL-CN, TPL-CR, TPL-CV and TPL-CZ