

Sealants, Adhesives & Tri-Flow Lubricant



White Lightning® Silicone Sealant



PART #	MSDS REF#	DESCRIPTION	STD PK	TUBE SIZE
37530	WL9010	100% RTV Silicone Sealant Clear	12	10 oz
37531	WL9210	100% RTV Silocone Sealant White	12	10 oz

- Provides a watertight seal.
- Use for interior and exterior projects.
- Highly, permanently flexible.
- Will not crack, crumble or shrink.
- Resists moisture and mildew.
- Excellent adhesion to non-porous materials.
- NSF compliant.
- Complies with TT-S-00230C, TTS-001543A, ASTM C-920.

Sprayon® Clear Silicone



PART #	DESCRIPTION	NET FILL	STD PK
96070	RTV Clear Silicone Sealant	7.25 oz	6 cans

- Chemically stable.
- Shows little change in physical properties after exposure to sunlight, rain, snow, ozone, temperature extremes and weathering.
- Mildew resistant.
- Long tooling time of 5-10 minutes.
- P1 rated, NSF registered.

Tri-Flow® Lubricants with P.T.F.E.



PART #	MSDS REF#	DESCRIPTION	CONTAINER	CAN SIZE	NET FILL
37514	TF20025	Industrial Lubricant	Aerosol Can	12	6 oz
37515	TF29200	Industrial Lubricant	Trigger Spray Bottle	6	18 oz
37516	TF21010	Industrial Lubricant	Non-Aerosol	12	2 oz

- Lubricates with oils, additives and P.T.F.E. to reduce friction and increase part life.
- Penetrates inaccessible areas to displace contaminants.
- Rejects dirt, dust, and other abrasive particles.
- Effective from -60° to 475°F.
- H2 rated, NSF registered.
- Offers 10 times as much load capacity as WD-40 in a standard Falex-Load Text (ASTM D-3233b).

Uses:

- Machinery
- Conveyors
- Bearings
- Cables
- Gears