

Vigilant® H2 Series LED High Bay

Ordering Information and Mounting Accessories

Part Number	Fixture Lumen	Watt	LPW	Wet Location	Voltage	CCT	Lens	Light Distribution Pattern
Standard Models								
H2GMC4NN-SNG	25,250	180	140	IP66	110 - 277V AC	5000K (cool white)	Tempered glass	Circular
H2GMC5NN-SNG	25,250	200	126	IP66	347V AC	5000K (cool white)	Tempered glass	Circular
H2GMC5NN-SNG	25,250	192	132	IP66	480V AC	5000K (cool white)	Tempered glass	Circular
Variable Dimming Models								
H2GMC4ND-SNG	25,250	180	140	IP66	110 - 277V AC	5000K (cool white)	Tempered glass	Circular

All values typical unless otherwise stated, Lumen values are typical (tolerance +/- 10%)

For models needing a Safety Bracket, replace the 10th character with a **S**. Example H2GMC4NN-SNG becomes H2GMC4NN-SSG



HBXW3-SSL-316
HBXW3-SSL-304

- Stainless Steel Bracket



HBXCAB48

- 48" long stainless steel safety rope (for use with safety bracket)




HBXDC

- 21° slope dust cover
- HBXDC45**
- 45° slope dust cover
- HBXDC60**
- 60° slope dust cover



HBXW3-SSL-304FT

- 304 Stainless steel forward throw bracket



HBXTH347480

- Top hat with 347-480V AC step down transformer (consult factory when using with hook or loop)



HBXH

- Hook




HBXW2

- Swivel bracket and cable gland
- HBXW3**
- Swivel bracket



HBXL

- Loop



HBXDUALBRCKT

- Dual bracket



HBXCU

- Ceiling / wall mount



HBXLENGC

- Clear tempered glass
- HBXLENPC**
- Polycarbonate lens, clear
- HBXLENAC**
- Acrylic lens, clear

Vigilant® LED High Bay

Ordering Information and Mounting Accessories

Part Number	Fixture Lumen	Watt	LPW	Wet Location	Voltage	CCT	Lens	Light Distribution
Powerwash Models								
HEGMC4PN-SPG	26,500	212	125	1000 PSI	110 - 277V AC	5000K (cool white)	Tempered glass	Medium
HEGRC4PN-SPG	26,500	212	125	1000 PSI	110 - 277V AC	5000K (cool white)	Tempered glass	Wide
HEGMC4KN-SPG	18,000	144	125	1000 PSI	100 - 277V AC	5000K (cool white)	Tempered glass	Medium
HEGRC4KN-SPG	18,000	144	125	1000 PSI	100 - 277V AC	5000K (cool white)	Tempered glass	Wide
HEGMC4GN-SPG	14,000	112	125	1000 PSI	100 - 277V AC	5000K (cool white)	Tempered glass	Medium
HEGRC4GN-SPG	14,000	112	125	1000 PSI	100 - 277V AC	5000K (cool white)	Tempered glass	Wide
HEGMC4DN-SPG	11,000	88	125	1000 PSI	100 - 277V AC	5000K (cool white)	Tempered glass	Medium
HEGRC4DN-SPG	11,000	88	125	1000 PSI	100 - 277V AC	5000K (cool white)	Tempered glass	Wide

All values typical unless otherwise stated, Lumen values are typical (tolerance +/- 10%).

All models shown in the table are Cool White, for models in Neutral White, 4000K CCT, replace the 5th character with an **N**. Ex: HEGMC4PN-SNG becomes HEGMC4PN-SNG. Deduct 5% from lumen values when specifying neutral.

For models needing a Safety Bracket, replace the 10th character with an **S**. Example HEGMC4PN-SNG becomes HEGMC4PN-SNG.

All models show in the above table come with an internal fuse. For models needing an external fuse, replace the 10th character with a **F**. Ex: HEGMC4PN-SNG becomes HEGMC4PN-SFG. (Fixture will be listed damp location only with internal fuse).

For models needing both Safety Bracket & Fuse, replace the 10th character with an **SF**. Ex: HEGMC4PN-SNG becomes HEGMC4PN-SFG.

Part numbers with occupancy sensor that will be installed with Hook or Loop (HBXH or HBXL) accessories will require a counter balance installed prior to shipment. Replace the 10th character with an **C**. Ex: HEGMC4PN-SNG becomes HEGMC4PN-SNG.

Part numbers listed in the tables above come with a glass lens. For models needing a polycarbonate dome lens, replace the 3rd character with an **L**. Ex: HEGMC4PN-SNG becomes HELMC4PN-SNG. For models needing a flat polycarbonate lens, replace the 3rd character with a **2**. Ex: HEGMC4PN-SNG becomes HE2MC4PN-SNG. For models needing a flat acrylic lens, replace the 3rd character with an **1**. Ex: HEGMC4PN-SNG becomes HE1MC4PN-SNG. Dome & acrylic lens not available on power wash models, please use glass or flat polycarbonate.



HBXW3-SSL-316
HBXW3-SSL-304

- Stainless steel bracket



HBXCAB48

- 48" long stainless steel safety rope (for use with safety bracket)




HBXDC

- 21° slope dust cover
- HBXDC45**
- 45° slope dust cover
- HBXDC60**
- 60° slope dust cover



HBXW3-SSL-304FT

- 304 Stainless steel forward throw bracket



HBXTH347480

- Top hat with 347-480V AC step down transformer



HBXH

- Hook



HBXW2

- Swivel bracket and cable gland

HBXW3

- Swivel bracket



HBXL

- Loop




HBXDUALBRCKT

- Dual bracket



HBXCU

- Ceiling / wall mount



HBXREF22

- 22" Acrylic reflector (must be ordered with high bay, not a retrofit option)



HBXCG

- Cable gland



HBXLENGC

- Clear tempered glass

HBXLENPC

- Polycarbonate lens, clear

HBXLENAC

- Acrylic lens, clear



LBXLENP

- Polycarbonate dome lens replacement

DuroSite® LED High Bay

Ordering Information and Mounting Accessories

Part Number	Fixture Lumen	Wattage	LPW	Warranty	Voltage	CCT	Lens		Light Distribution Pattern
							Clear	Diffused	
Occupancy Sensor Models - 347 - 480V AC									
HBGC8T	14,000	161	87	5yr	347 - 480V AC	5000K (cool white)	Tempered glass		Circular
HBLC8T	10,750	146	74	5yr	347 - 480V AC	5000K (cool white)		Polycarbonate dome	Circular
HB6C8T	11,750	146	80	5yr	347 - 480V AC	5000K (cool white)	Tempered glass		Aisle
HB7C7T	11,750	146	80	5yr	347 - 480V AC	5000K (cool white)	Tempered glass		Aisle
HB7C8T	11,750	146	80	5yr	347 - 480V AC	5000K (cool white)	Polycarbonate		Aisle
HB1C8T	11,500	146	79	5yr	347 - 480V AC	5000K (cool white)	Acrylic		Circular
HB1C7S	11,500	146	79	5yr	347 - 480V AC	5000K (cool white)	Acrylic		Circular
HB1C8S	11,500	146	79	5yr	347 - 480V AC	5000K (cool white)	Acrylic		Circular
HB2C7T	10,750	146	74	5yr	347 - 480V AC	5000K (cool white)	Polycarbonate		Circular
HB2C8T	10,750	146	74	5yr	347 - 480V AC	5000K (cool white)	Polycarbonate		Circular
HB5C7S	10,500	146	72	5yr	347 - 480V AC	5000K (cool white)		Acrylic	Circular
HB2C7S	10,500	146	72	5yr	347 - 480V AC	5000K (cool white)	Polycarbonate		Circular
HB2C8S	10,500	146	72	5yr	347 - 480V AC	5000K (cool white)	Polycarbonate		Circular
HB4C7R	8,500	124	69	5yr	347 - 480V AC	5000K (cool white)		Polycarbonate	Circular
HB4C8R	8,500	124	69	5yr	347 - 480V AC	5000K (cool white)		Polycarbonate	Circular

All values typical unless otherwise stated, Lumen values are typical (tolerance +/- 10%).



HBXW3-SSL-316
HBXW3-SSL-304

- Stainless steel bracket



HBXCAB48

- 48" long stainless steel safety rope (for use with safety bracket)



HBXDC

- 21° slope dust cover

HBXDC45

- 45° slope dust cover

HBXDC60

- 60° slope dust cover



FLX1HBXSS

- 304 Stainless steel forward throw bracket



HBXTH347480

- Top hat with 347-480V AC step down transformer (consult factory when using with hook or loop)



HBXH

- Hook



HBXW2

- Swivel bracket and cable gland


HBXW3

- Swivel bracket



HBXL

- Loop



HBXDUALBRCKT

- Dual bracket



HBXCU

- Ceiling / wall mount



HBXREF22

- 22" Acrylic reflector (must be ordered with high bay, not a retrofit option)



HBXCG

- Cable gland



HBXLENGC


- Clear tempered glass

HBXLENAC

- Acrylic lens, clear

HBXLENAD

- Acrylic lens, diffused



HBXLENPC

- Polycarbonate lens, clear

HBXLENPD

- Polycarbonate lens, diffused

DuroSite® LED Low Bay

Ordering Information and Mounting Accessories

Part Number	Fixture Lumen	Wattage	LPW	Warranty	Voltage	CCT	Lens	Optical Pattern
Standard Models - 100 - 277V AC								
HBWC4L	8,500	107	79	10yr	100 - 277V AC	5000K (cool white)	Polycarbonate dome	Wide
LBW1C1D	6,000	80	75	5yr	100 - 277V AC	5000K (cool white)	Polycarbonate dome	Wide
LBW1C1D-10YR	5,500	70	79	10yr	100 - 277V AC	5000K (cool white)	Polycarbonate dome	Wide
LBW1C1A	3,800	45	84	5yr	100 - 277V AC	5000K (cool white)	Polycarbonate dome	Wide
Standard Models - 347 - 480V AC								
HBWC5L	8,500	107	79	5yr	347-480V AC	5000K (cool white)	Polycarbonate dome	Wide
LBW1C7D	6,000	80	75	5yr	347-480V AC	5000K (cool white)	Polycarbonate dome	Wide
Occupancy Sensor Models - 120 - 277V AC								
LBW1C2D	6,000	80	75	5yr	120-277V AC	5000K (cool white)	Polycarbonate dome	Wide
LBW1C2A	3,800	45	84	5yr	120-277V AC	5000K (cool white)	Polycarbonate dome	Wide
LBW1C2ACB	3,800	45	84	5yr	120-277V AC	5000K (cool white)	Polycarbonate dome	Wide
Variable Dimming Models - 100 - 277V AC								
LBW1C5D	6,000	80	75	5yr	100-277V AC	5000K (cool white)	Polycarbonate dome	Wide
LBW1C5A	3,800	45	84	5yr	100-277V AC	5000K (cool white)	Polycarbonate dome	Wide

All values typical unless otherwise stated, Lumen values are typical (tolerance +/- 10%).



HBXW2

- Swivel bracket and cable gland

HBXW3

- Swivel bracket



HBXL

- Loop



HBXH

- Hook



HBXCU

- Ceiling / wall mount



LBXLENP

- Polycarbonate dome lens replacement



HBXCG

- Cable Gland