


DuroSite® LED Floodlight

Ordering Information and Mounting Accessories

Part Number	Fixture Lumen	Watt	LPW	Warranty	Voltage	Lens	CCT	Light Distribution
Standard Models - 100 - 277V AC								
FLW466NC4NG	15,000	130	115	10yr	100-277V AC	Tempered glass	5000K (cool white)	Very wide (115°)
FLW476NC4NG	14,750	130	113	10yr	100-277V AC	Tempered glass	5000K (cool white)	Asymmetrical (140° x 115°)
FLW467NC4NG	14,750	130	113	10yr	100-277V AC	Tempered glass	5000K (cool white)	Asymmetrical (115° x 140°)
FLW455NC4NG	14,500	140	104	10yr	100-277V AC	Tempered glass	5000K (cool white)	Wide (93°)
FLW444NC4NG	14,500	140	104	10yr	100-277V AC	Tempered glass	5000K (cool white)	Medium (52°)
FLW422NC4NG	13,500	140	96	10yr	100-277V AC	Tempered glass	5000K (cool white)	Narrow (23°)
FLW276NC2NG	11,500	109	105	10yr	100-277V AC	Tempered glass	5000K (cool white)	Asymmetrical (140° x 115°)
FLW267NC2NG	11,500	109	105	10yr	100-277V AC	Tempered glass	5000K (cool white)	Asymmetrical (115° x 140°)
FLW266NC2NG	11,250	109	103	10yr	100-277V AC	Tempered glass	5000K (cool white)	Very wide (115°)
FLW255NC2NG	11,000	109	101	10yr	100-277V AC	Tempered glass	5000K (cool white)	Wide (93°)
FLW244NC2NG	10,500	109	96	10yr	100-277V AC	Tempered glass	5000K (cool white)	Medium (52°)
FLW222NC2NG	10,750	109	99	10yr	100-277V AC	Tempered glass	5000K (cool white)	Narrow (23°)
Standard Models - 347 - 480V AC								
FLW276NC5NG	11,750	113	104	10yr	347-480V AC	Tempered glass	5000K (cool white)	Asymmetrical (140° x 115°)
FLW266NC5NG	11,250	113	100	10yr	347-480V AC	Tempered glass	5000K (cool white)	Very wide (115°)
FLW255NC5NG	10,000	112	89	10yr	347-480V AC	Tempered glass	5000K (cool white)	Wide (93°)
FLW244NC5NG	10,000	112	89	10yr	347-480V AC	Tempered glass	5000K (cool white)	Medium (52°)
FLW222NC5NG	10,000	112	89	10yr	347-480V AC	Tempered glass	5000K (cool white)	Narrow (23°)

All values typical unless otherwise stated, Lumen values are typical (tolerance +/- 10%).

Part numbers listed in the table above are powder coated gray. For bronze powder, coat replace the 10th character with **Z**. FLW244NC2**NG** becomes FLW244NC2**ZG**



FLX-3RPA-20DB

- Reducer for 3" OD round pole top to 2-3/8" light mount


FLX-4RPA-20DB

- Reducer for 4" OD round pole top to 2-3/8" light mount



HZXGBL2

- Safety cable Kit



FLX-4SPA-20DB

- Internal tenon adapter for 4" square pole top to 2-3/8" light mount

FLX-5SPA-20DB

- 5" square pole top to 2-3/8" light mount

FLX-6SPA-20DB

- 6" square pole top to 2-3/8" light mount




FLX-1TPT-20DB

- Tenon pole topper, 2-3/8" mount



FLX-1RAB-20DB

- Tenon pole topper, 2-3/8" mount



FLX-2RSR-20DB

- Round square round bracket for 2 lights, 2-3/8" mount, 21" spacing




FLX-2LBH-20DB

- Bull horn for 2 lights, 2-3/8" mount, 21" spacing



FLX-3LBH-20DB

- Bull horn for 3 lights, 2-3/8" mount, 21" spacing



FLX-3RSR-20DB

- Round square round bracket for 3 lights, 2-3/8" mount, 21" spacing




FLX-4LBH-20DB

- Bull horn for 4 lights, 2-3/8" mount, 21" spacing



FLX-4RBH-20DB

- Bull horn for 4 lights in star configuration, 2-3/8" mount, 21" spacing



FLX-4RSR-20DB

- Round square round bracket for 4 lights, 2-3/8" mount, 21" spacing