



Miniature Lamps

EIKO offers one of the widest lines of miniature lamps in the industry. Featuring quality construction with durable design, our lamps meet or exceed SAE and/or ANSI specifications for lumen output and lifetime hours and are known for their long-term reliability. Our in-house testing facilities ensure product quality. Available in traditional incandescent lamps or energy-efficient LED lamps that feature extraordinary long life.

LED Miniature Lamps

Order Code	Item	Volts	Base	Bulb	MOL in/ mm	MOD in/ mm	Lumens	Life/Hrs
02697	LED-24-MF-R*	24~28 VAC/DC	Midget Flanged (SX6s)	T-1 3/4	0.63/16	0.24/6	0.7	30,000
02698	LED-24-MF-W	24~28 VAC/DC	Midget Flanged (SX6s)	T-1 3/4	0.63/16	0.24/6	3.2	30,000
02702	LED-24-MG-W	24~28 VAC/DC	Midget Grooved (S5.7s)	T-1 3/4	0.63/16	0.24/6	1.1	30,000
02688	LED-14-BA9S-R	14 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.75	30,000
02687	LED-14-BA9S-G	14 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	1.5	30,000
02689	LED-14-BA9S-W	14 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	2.4	30,000
02694	LED-24-BA9S-R	24~28 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.7	30,000
02696	LED-24-BA9S-Y	24~28 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.6	30,000
02693	LED-24-BA9S-G	24~28 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	1.5	30,000
02695	LED-24-BA9S-W	24~28 VAC/DC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	2.4	30,000
02679	LED-120-MB-R	110~130 VAC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.2	30,000
02682	LED-120-MB-Y	110~130 VAC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.2	30,000
02678	LED-120-MB-G	110~130 VAC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.5	30,000
02681	LED-120-MB-W	110~130 VAC	Miniature Bayonet (BA9s)	T-3 1/4	1.0/25	0.40/10	0.6	30,000
02705	LED-24-PSB-R	24~28 VAC/DC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.4	30,000
02706	LED-24-PSB-W	24~28 VAC/DC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	1.1	30,000
02707	LED-24-PSB-Y	24~28 VAC/DC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.4	30,000
02704	LED-24-PSB-G	24~28 VAC/DC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.9	30,000
02684	LED-120-PSB-R	110~130 VAC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.2	30,000
02686	LED-120-PSB-Y	110~130 VAC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.2	30,000
02683	LED-120-PSB-G	110~130 VAC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.6	30,000
02685	LED-120-PSB-W	110~130 VAC	Slide Base 5 (TS5)	T-2	1.1/28	0.27/6.8	0.9	30,000
02691	LED-14-T1.75 WEDGE-W	14 VAC/DC	Sub-Miniature Wedge (W2.1x4.6d)	T-1 3/4	0.77/19.4	0.22/5.5	1.1	30,000
02709	LED-24-T1.75 WEDGE-R*	24~28 VAC/DC	Sub-Miniature Wedge (W2.1x4.6d)	T-1 3/4	0.77/19.4	0.22/5.5	0.1	30,000
02711	LED-24-T1.75 WEDGE-W	24~28 VAC/DC	Sub-Miniature Wedge (W2.1x4.6d)	T-1 3/4	0.77/19.4	0.22/5.5	1.1	30,000
02712	LED-24-T1.75 WEDGE-Y*	24~28 VAC/DC	Sub-Miniature Wedge (W2.1x4.6d)	T-1 3/4	0.77/19.4	0.22/5.5	.3	30,000
05394	LED-12-SCBAY-W	12 VAC/DC	SC Bayonet (BA15s)	S-8	1.28/32.6	0.73/18.5	21.6	10,000
05379	LED-12-DCBAY-W	12 VAC/DC	DC Index Bayonet (BAY15d)	S-8	1.81/46	1.0/25	21.6/7.8	10,000

Continued on next page >>>

Miniature

Order Code	Item	Volts	Amps	Base	Bulb	Filament	MOL in/ mm	MOD in/ mm	Lumens	Life/Hrs
16044	555-G	6.3	0.25	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2R	1.06/26.9	0.40/10.2		3,000
16045	555-R	6.3	0.25	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2R	1.06/26.9	0.40/10.2		3,000
16046	555-Y	6.3	0.25	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2R	1.06/26.9	0.40/10.2		3,000
44017	24E1	24	0.035	Slide Base 1 (TS1)	T-2	C-2F	1.69/42.9	0.27/6.9	189	10,000
49731	1028.09.527-501	130	0.02	Miniature Bayonet (BA9s)	T-3 1/4	2C-2F	1.19/30.2	0.43/11.0	4.02	20,000
00025	47-B	6.3	0.15	Miniature Bayonet (BA9s)	T-3 1/4	C-2R	1.19/30.2	0.43/11.0		3,000
00027	47-R	6.3	0.15	Miniature Bayonet (BA9s)	T-3 1/4	C-2R	1.19/30.2	0.43/11.0		3,000
00028	47-Y	6.3	0.15	Miniature Bayonet (BA9s)	T-3 1/4	C-2R	1.19/30.2	0.43/11.0		3,000
00356	906G*	13	0.69	Miniature Wedge (W2.1x9.5d)	T-5	C-2F	1.49/37.9	0.62/15.8		1,000
00357	906R	13	0.69	Miniature Wedge (W2.1x9.5d)	T-5	C-2F	1.49/37.9	0.62/15.8		1,000
00358	906B	13	0.69	Miniature Wedge (W2.1x9.5d)	T-5	C-2F	1.49/37.9	0.62/15.8		1,000
05584	K010XE/F*	13.5	0.37	SV8.5mm	Festoon 10mm	C-8	1.73/44.0	0.40/10.0	50	5,000
05586	K016XE/F*	13.5	0.74	SV8.5mm	Festoon 10mm	C-8	1.73/44.0	0.40/10.0	120	5,000
05588	K020XE/F*	26	0.192	SV8.5mm	Festoon 10mm	C-8	1.73/44.0	0.40/10.0	50	5,000
49503	7362	5	0.115	Bi-Pin .125 (G3.17)	T-1 3/4	C-2R	0.63/16.0	0.23/5.9	189	40,000
00613	1446	12	0.2	Miniature Screw (E10)	G-3 1/2	C-2V	0.94/23.9	0.43/11.0	21.37	250
00618	1480	18	0.17	Candelabra Screw (E12)	T-4	C-7A	1.97/50.0	0.54/39.1	25	1,500
49627	1680	6	4.1	SC Bayonet (BA15s)	S-8	C-6	2.00/50.8	1.04/26.4	400	300
06431	PC37	14	0.09	Printed Circuit socket (P8.25d)	T-1 3/4	C-2F	0.82/20.8	0.23/5.9	6.29	2,500
05590	K023XE/F*	26	0.385	SV8.5mm	Festoon 10mm	C-8	1.73/44.0	0.40/10.0	120	3,000
16026	2102	18	0.04	Wire Leads (WL)	T-1 3/4	C-2F	0.52/13.2	0.23/5.9	189	10,000
01034	267	6.3	0.15	Miniature Bayonet (BA9s)	T-3 1/4	C-2R	1.19/30.2	0.43/11.0	4.15	5,000
16024	20-99	13	1.08	SC Bayonet (BA15s)	G-16.5	C-6	3.00/76.2	2.12/53.9	150	1,000
16025	20-99F	13	1.08	SC Bayonet (BA15s)	G-16.5	C-6	3.00/76.2	2.12/53.9		1,000
49053	2841	24	0.125	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2V	1.06/26.9	0.40/10.2	22.12	1,000
01183	338	2.7	0.06	Midget Flanged (SX6s)	T-1 3/4	C-2R	0.63/16.0	0.23/5.9	0.50	6,000
01185	342	6	0.04	Midget Screw (E5)	T-1 3/4	C-2R	0.63/16.0	0.23/5.9	0.38	10,000
49460	35A2	35	0.04	Slide Base 2 (TS2)	T-2	C-2F	1.69/42.9	0.27/6.9		7,500
05198	44-A	6.3	0.25	Miniature Bayonet (BA9s)	T-3 1/4	C-2R	1.19/30.2	0.43/11.0		3,000
01347	44-B	6.3	0.25	Miniature Bayonet (BA9s)	T-3 1/4	C-2R	1.19/30.2	0.43/11.0		3,000
01349	44-G	6.3	0.25	Miniature Bayonet (BA9s)	T-3 1/4	C-2R	1.19/30.2	0.43/11.0		3,000
01351	44-R	6.3	0.25	Miniature Bayonet (BA9s)	T-3 1/4	C-2R	1.19/30.2	0.43/11.0		3,000
49634	456	28	0.17	Miniature Bayonet (BA9s)	G-4 1/2	C-2F	1.07/27.2	0.59/15.0	25	5,000
49462	45675	14	0.046	Bi-Pin .100 (G2.54)	T-1 1/4	C-2F	0.60/15.2	0.17/4.3	1.51	
05223	45685	14	0.06	Bi-Pin .100 (G2.54)	T-1 1/2	C-2F	0.60/15.2	0.19/4.8	0.38	
05203	555-P	6.3	0.25	Miniature Wedge (W2.1x9.5d)	T-3 1/4	C-2R	1.06/26.9	0.40/10.2		3,000
81173	718	5	0.115	Sub-Midget Flanged (SX4s)	T-1	C-2R	0.38/9.7	0.13/3.2	189	40,000
81145	7333	5	0.06	Midget Flanged (SX6s)	T-1 3/4	C-2R	0.63/16.0	0.23/5.9	0.63	25,000
01785	89K	13	0.58	Candelabra Screw (E12)	G-6	C-2R	1.38/35.1	0.75/19.1	75	750
01353	44-Y	6.3	0.25	Miniature Bayonet (BA9s)	T-3 1/4	C-2R	1.19/30.2	0.43/11.0		3,000
07753	PC119	14	0.15	Printed Circuit socket (P8.25d)	T-2 1/4	C-2V	2.28/58	0.28/7.14	15.08	3,000
07999	PC579	12.8	0.8	Printed Circuit socket (BI0d)	T-5	C-2R		0.62/15.8	115	200
49724	6614F-BP	14	0.05	Double End Cap (SF6/6)	T-2	C-8	1.26/32.0	0.24/6.1	2.01	10,000
43300	918-BP	12.8	0.56	Miniature Wedge (W2.1x9.5d)	T-5	C-2R	1.49/37.9	0.62/15.8	82	500
08305	949-BP	130	0.022	Miniature Bayonet (BA9s)	T-3 1/4	2C-2F	1.19/30.2	0.43/11.0	5.03	7,000
01763	8623	28	0.04		T-1 1/4					
01814	906A	13	0.69	Miniature Wedge (W2.1x9.5d)	T-5	C-2F	1.49/37.9	0.62/15.8	75	1,000
00723	1820R	28	0.1	Miniature Bayonet (BA9s)	T-3 1/4	C-2F	1.19/30.2	0.43/11.0	20.11	1,000