



## EL-2SQL LED Series

LED Thermoplastic 3.6V Ni-Cd  
Battery Unit

TYPE: \_\_\_\_\_  
CATALOG #: \_\_\_\_\_  
NOTES: \_\_\_\_\_

### Features

- Injection-molded UV stabilized thermoplastic housing and back plate
- Innovative, snap together design allows for fast installation
- Universal knock-out pattern on the back plate allows for junction box mounting
- Ceiling or wall-mount
- Two fully adjustable glare-free 1W LED heads
- Each unit provides 200 lumens, LED CCT 6000K
- Damp Location listing is standard in all models
- 3.6V-3W maintenance free Ni-Cd battery
- EL-2SQLR series is offered with 3.6V-3W remote capacity for the EF47DSQL or EL12D-LED series remote
- Remote capacity model EL-2SQLRAD available with advanced diagnostics
- 120/277VAC dual voltage operation
- LED indicator light and push button test switch
- Low voltage battery disconnect
- UL 924 Listed
- Damp Location listing is standard on all models
- UL 94, 5VA flame rated
- Unit has a three-year full warranty


Detailed warranty terms located at: [www.emergi-lite.com/usa/files/EL\\_Warranty.pdf](http://www.emergi-lite.com/usa/files/EL_Warranty.pdf)

### Accessories (order as a separate item)

DESCRIPTION	SUFFIX
Replacement battery for EL-2SQL	022433-E
Replacement battery for EL-2SQLR & EL-SSQLRAD	2 X 022433-E
Vandal shield	VRS.BB
Vandal shield (NEMA 4X)	VRSBB.4X
Wire Guard (heads in any position)	WG10-E

### Dimensions

Dimensions are approximate and subject to change.



### Unit Rating

Series	DC SPECS		AC SPECS
	Battery Type	DC Voltage	Units Dual Voltage*
EL-2SQL	Ni-Cd	3.6V	120/277, 60Hz, 0.024A
EL-2SQLR		3.6V	120/277, 60Hz, 0.028A
EL-2SQLRAD		3.6V	120/277, 60Hz, 0.028A

\* National Electrical Code Specification

### How to Order

SERIES	HEAD STYLE/ LAMP	OPTIONS
EL= Self-Powered	-2SQL	Blank= No option R= Remote Capacity* RAD= Remote Capacity and Advanced Diagnostics*  * To be used with EF47DSQL or EF12D-LED only.

Example: **EL-2SQLRAD**

## EF47DSQL Series

Thermoplastic Square LED  
Indoor Remote Heads



### Features

- Thermoplastic dual head remote
- LED 3.6V, 2W total
- 6000K LED color
- Wall or ceiling mount
- Damp Location
- UL924 Listed
- 3 Year Full warranty

Detailed warranty terms located at: [www.emergi-lite.com/usa/files/EL\\_Warranty.pdf](http://www.emergi-lite.com/usa/files/EL_Warranty.pdf)


### How to Order

SERIES	NO. OF LAMP	OPTIONS
EF47	D= Double head	SQL= Thermoplastic Square LED head

Example: **EF47DSQL**

### Dimensions

Dimensions are approximate and subject to change.



## EF12D-LED Series

Thermoplastic Square LED  
Outdoor Remote Heads



### Features

- EF12D-LED remote series is multi-volt 3.6, 6 or 12V, 3W in total
- Thermoplastic housing and aluminum canopy with fully adjustable LED heads
- Available only in Gray 2-heads configuration
- Suitable for outdoor, wet location applications
- Wall or ceiling mount
- UL924 Listed
- 3 Year Full warranty

Detailed warranty terms located at: [www.emergi-lite.com/usa/files/EL\\_Warranty.pdf](http://www.emergi-lite.com/usa/files/EL_Warranty.pdf)

### How to Order

SERIES	NO. OF LAMP	OPTIONS
EF12	D= Double head	-LED= Thermoplastic Square LED head

Example: **EF12D-LED**

### Dimensions

Dimensions are approximate and subject to change.

