

TEMPORARY DELUXE CORDLIGHTS

Temporary Construction Lighting Strings are intended for severe environments and are impervious to dust, dirt, chemical vapors, salt spray and other corrosive elements. Constructed of heavy-duty 14/2, 14/3 or 12/3 SJTW round cord with a 75°C (167°F) temperature rating, our Deluxe CordLights are UL Listed and complies with UL Standard 1088 for Temporary Lighting Strings.

- File Number: E190858. Meets all OSHA Standards.
- Meets the requirements of the 2014 National Electrical Code: Article 590.4(F).
- Suitable for indoor and outdoor use.
- Weather-resistant lamp sockets feature rigid-mounted eyelets for hooks or wire to expedite and simplify hanging.
- Unique open and secure closure clasp on the heavy-duty Safety Cage easily facilitates bulb changes.
- A patented detent “snap-off, snap-on” fitting on the lamp socket enables quick replacement if the Safety Cage becomes damaged.
- Rated only for use with Type A23 Incandescent Lamp - 150-watt rating (maximum), Compact Fluorescent (23-watts and above) or LED Lamps (1000 lumens and above).
- U.S. Patent Number: D.439,697.



Typical Applications for Temporary Deluxe CordLights:

- Construction Sites
- Parking Lots
- Walkways
- Festivals
- Circus Tents
- Christmas Tree Lots

Catalog Number	UPC Number	Description	Order Unit	Unit Qty	Unit Pkg	Units/Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
16010†	16010	Deluxe CordLights: 14/2 SJTW Round Cord, 100-FT Length, 10-FT Centers (without Plug) - Yellow	EA	1	BX	0	0	1	No	13
16301	16301	Deluxe CordLights: 14/3 SJTW Round Cord, 100-FT Length, 10-FT Centers (with Molded Plug) - Yellow	EA	1	BX	0	0	1	No	14
16350	16350	Deluxe CordLights: 12/3 SJTW Round Cord, 100-FT Length, 10-FT Centers (without Plug) - Yellow	EA	1	BX	0	0	1	No	19
16353	16353	Deluxe CordLights: 12/3 SJTW Round Cord, 100-FT Length, 10-FT Centers (with Molded Plug) - Yellow	EA	1	BX	0	0	1	No	19
16100	16100	Replacement Safety Cage: for Deluxe CordLight - Yellow	EA	1	BN	10	10	10	Yes	1

†UL 1088 - Article 17.2 – lamp guard shall be constructed of polymeric material. The actual molded product is polypropylene. Flame class is V-0 meets UL 746C.

UNITS OF MEASURE KEY

Order Unit: The Unit to be ordered; Order Qty: Number of pieces in each Unit; Unit Pkg: Packaging types - BG (Bag), BX (Box), BN (Bulk); Units/Case: Unit packages contained in the Case; TL Case Qty: The total number of items in each Master Case; Min Order Qty: The smallest Unit that can be ordered; MM Req: Must order multiples of the Unit in the stated quantities; Ship Wt (Lbs): Total weight of the units per Carton

Specifications subject to change without prior notice.