

Eaton FWP-32G22FI

Catalog Number: FWP-32G22FI

Eaton Bussmann series FWP high speed fuse, 690V, 32A, 200 kAIC, With Indicator, High speed fuse, Ferrule end X ferrule end - FWP-32G22FI

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-32G22FI
	UPC
	051712689748
EAN	Product Length/Depth
5027590500685	58 mm
Product Height	Product Width
22 mm	22 mm
Product Weight	Warranty
52.9 g	No warranty
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	IEC Rated



Product specifications

Interrupt rating

200 kAIC

Release characteristic

Other

Amperage Rating

32 A

Frequency rating - max

62 Hz

Fuse type

FWP-G22FI

Accessories

CH22 Modular fuse holder

Fitted with:

Striker

Fuse size

22 x 58 mm

Voltage rating

690 V

Fuse indicator

Top fuse status indicator

Construction size

22 mm x 58 mm

Clearing (I2T)

616

Connection

Ferrule end x ferrule end

Material

Ceramic

Utilization category

gR (general purpose semiconductor protection)

Watt losses

9.21 W

Type

High speed fuse

Fuse shape

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA High-speed, cylindrical gR fuse-links

CE High-speed, cylindrical gR fuse-links

Technical data sheets

10469 22 x 58 mm gR cylindrical fuse links

Cylindrical

Breaking capacity

200 kA

Frequency rating - min

45 Hz

Class

Class gR

Pre arc (I2T)

97

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)