

STUD PUNCHES

ESP710L Stud Punch



ESP710L11

- This tool punches 1-11/32" (34.1 mm) diameter holes in 16 and 18 gauge structural studs
- Has the ability to punch holes in under 5 seconds
- The ESP710L can take both time and hard work out of the stud punching process
- 4" Throat Depth from center of punch

| CAT. NO. | UPC NO. | DESCRIPTION |
|-----------|---------|------------------------------|
| ESP710L11 | 52165 | Punch, Stud Bat 120V Charger |

BATTERY-POWERED STUD PUNCH

| CAT. NO. | UPC NO. | ACTUAL HOLE SIZE | | WEIGHT | | LENGTH | | HEIGHT | | CAPACITY | | BATTERY | CHARGER |
|-----------|---------|------------------|------|--------|-----|--------|-----|--------|-----|----------|-----|-------------------|----------|
| | | IN. | MM | LBS. | KG | IN. | MM | IN. | MM | GA | MM | | |
| ESP710L11 | 52165 | 1-11/32 | 34.1 | 9.2 | 4.2 | 15 | 381 | 11-3/4 | 298 | 16 | 1.5 | 3.0Ah 18V, Li-Ion | 120 Volt |

Metal Stud Punches



709

- Punch up through 20 gauge (0.9 mm) steel studs in one stroke
- Aluminum head provides strength with minimum weight, and reducing operator fatigue
- Contoured handle design gives better operator leverage and makes it possible to punch in tight places
- Self-stripping design eliminates punch hang-ups
- Automatically centers holes on standard studs
- Conversion kit available to upgrade early models from 24 gauge to 20 gauge maximum capacity

| CAT. NO. | UPC NO. | DESCRIPTION | WEIGHT | |
|----------------|---------|---|--------|-----|
| | | | LBS. | KG |
| 709 | 22280 | 7/8" (22.2 mm) Diameter Stud Punch | 7 | 3.2 |
| 710 | 21285 | 1-11/32" (34.1 mm) Diameter Stud Punch | 7.5 | 3.5 |
| 30968 | 30968 | Conversion Kit – Upgrades Early Model 709 or 710 from 24 to 20 Gauge Maximum Capacity | | |
| R 121AV | 04006 | Punch for 709 | | |
| R 22286 | 22286 | Die for 709 | | |
| R 24823 | 24823 | Punch for 710 | | |
| R 21297 | 21297 | Die for 710 | | |
| 06015 | 06015 | Pin Kit | | |
| 36617 | 36617 | Link | | |
| 05932 | 05932 | Link and Pin Kit (709/710) | | |
| 21557 | 21557 | Compression Spring | | |

SPECIFICATIONS

| | |
|-----------------|--|
| Capacity | 709 - 1-5/8" (41.3 mm) and wider studs. 20 gauge (0.9 mm) steel studs. 710 - 2-1/2" (63.4 mm) and wider studs. 20 gauge (0.9 mm) steel studs. |
|-----------------|--|

Bushings for Metal Stud Punches



712A1000



711C

- Triple lock design holds bushing securely
- Locks securely into metal studs from 24 gauge to 12 gauge (0.6 mm to 2.5 mm)
- Helps protect wire insulation from sharp edges of metal studs
- Makes pulling smooth and easy by preventing hang-ups of cable on raw metal edges

| CAT. NO. | UPC NO. | DESCRIPTION | WEIGHT | |
|----------|---------|--|--------|-----|
| | | | LBS. | KG |
| 711C | 22288 | 100 Bushings for Hole Punched by 709 for 7/8" (22.2 mm) Diameter Hole | .5 | .23 |
| 711M | 22289 | 1,000 Bushings for Hole Punched by 709 for 7/8" (22.2 mm) Diameter Hole | 3.7 | 1.7 |
| 712A100 | 05927 | 100 Bushings for Pre-Punched Hole or 1-11/32" (34.1 mm) Diameter Hole Punched by 710 | 1.4 | .64 |
| 712A1000 | 05928 | 1,000 Bushings for Pre-Punched Hole or 1-11/32" (34.1 mm) Diameter Hole Punched by 710 | 15.5 | 7.0 |