LATCH CAM REMOVAL

- 1. Use pliers as shown.
- 2. Squeeze tabs on latch cam with pliers.
- 3. Lift latch cam and push in direction shown.



A Pentair Company

Hoffman Enclosures Inc. 2100 Hoffman Way Anoka, MN 55303–1745 (763) 422–2211 Tel www.hoffmanonline.com



87567340

Installation Instructions For Hollman Large Grounding Kit 99411400



A Pentair Company

Hoffman Enclosures Inc. 2100 Hoffman Wav Anoka, MN 55303-1745 (763) 422-2211 Tel www.hoffmanonline.com



- 1. Insert the 1/4-20x7/8 bolt through the hole in the panel as shown.
- 2. Secure bolt with keps nut. The keps nuts must penetrate into the paint to insure electrical continuity.
- 3. Attach the ground wire and secure with 1/4-20 hex nut as shown.
- 4. Install the lockwasher under one of the nuts securing the panel to insure grounding between the panel and the enclosure.
- 5. Attach grounding label included adjacent to the bolt as shown.

Installation Instructions For Large Grounding Kit 99411400

- 1. Secure keps nut on each ground stud. The keps nuts must penetrate into the paint to insure electrical continuity.
- 2. Attach the ground wire and secure with the 1/4–20 hex nuts as shown.
- 3. Attach the grounding labels included adjacent to the studs as shown.

