



## SystemOne Flush Covers

### Universal Flange and Cover Assembly

Carpet



Tile



- Hinged doors open 180° flush to the carpet flange or tile
- Locking studs allow each door to be secured independently
- The universal carpet or tile flange can be used for Hubbell SystemOne Floor Boxes and Fire-Rated Poke-Throughs
- Finishes and colors available:



Aluminum Finish



Brass Finish



Black



Gray




Ivory

### Features

- Durable cast aluminum construction available in black, gray, brass, aluminum and ivory powder coat finishes
- Features ScrubShield® technology that exceeds UL514 scrub water exclusion requirements
- Provides consistent look and maximum functionality throughout the installed life
- Meets ADA standards for accessible design

## SystemOne Flush Sub-Plates

Hubbell's modular sub-plate design allows users to economically upgrade Hubbell SystemOne FRPT and Floor Boxes to accommodate future moves, adds and changes. See page O-20 for additional Information.



4x4 Sub-Plate



Datacom and Power Sub-Plate



Extron® AAP/MAAP and Power Sub-Plate



Dual Style Line® Decorator Sub-Plate



Twist-Lock® Sub-Plate



Furniture Feed Cover, Carpet

### Features

- Durable cast aluminum construction, powder coat finish
- Hubbell 4X4: four 20A, 125V receptacles, four keystone openings for voice/data jacks and flush multimedia connectors
- Hubbell X-END and Hubbell iSTATION modular connectivity
- Accommodates Extron® Electronics Architectural Series audio/video system integration products
- Accommodates GFCI, surge and standard Style Line® Decorator receptacles
- Twist-Lock® receptacle with two flush keystone openings
- Large capacity and multi-service furniture feed applications
- Open system sub-plates permit maximum data flexibility

## Power Devices and Connectivity



Hubbell-PRO Receptacles



Hubbell iSTATION



Hubbell X-END



### Features

- Choose from Hubbell's industry leading selection of wiring devices for power services
- Hubbell iSTATION connectivity modules integrate with SystemOne to provide comprehensive multimedia solutions
- Hubbell X-END application cables and tails allow for more connectivity in a smaller footprint

Extron® is a registered trademark of Extron Electronics.

## SystemOne Flush Metal and Non-Metallic Floor Boxes and Covers, for Use In Concrete Floors

### Dimensions Inches (mm)

| Style  | Cast Iron   | Steel                                      | Steel AV                                   | Non-Metallic                             |
|--|---|--|--|--|
| <br>Metal | <br>Non-Metallic |  |  |  |
| Standard Corrosion-Resistant (On-grade)  | <b>S1CFB*</b><br>–  | <b>S1SFB*</b><br><b>S1SFBGR</b>            | <b>S1SFBV*</b><br><b>S1SFBVGR</b>          | <b>S1PFB</b><br>–                        |
| Min. Depth of Pour   | 3.50" (88.9)  | 3.50" (88.9)                               | 3.50" (88.9)                               | 3.00" (76.2)                             |
| Adjustability  | Fully   | Fully                                      | Fully                                      | Fully                                    |
| Cubic Inch (cm <sup>3</sup> ) Capacity   | 156.0 cu. in.<br>(2556.4 cm <sup>3</sup> )  | 175.7 cu. in.<br>(2879.2 cm <sup>3</sup> ) | 177.5 cu. in.<br>(2909.7 cm <sup>3</sup> ) | 100 cu. in.<br>(1638.7 cm <sup>3</sup> ) |
| Dimensions – A   | 3.00" (76.2)  | 3.00" (76.2)                               | 3.00" (76.2)                               | 6.00" (152.4)                            |
| Dimensions – B   | 7.26" (184.4)   | 7.50" (190.5)                              | 7.50" (190.5)                              | 5.58" (141.7)                            |
| Dimensions – C   | 7.45" (189.2)   | 7.38" (187.4)                              | 7.38" (187.4)                              | 7.08" (179.8)                            |
| Dimensions – D (Inside Diameter)   | 5.00" (127.0)   | 5.00" (127.0)                              | 5.00" (127.0)                              | 5.00" (127.0)                            |
| Power Entries  | 1" NPT Access Holes   | ¾", 1" Concentric KO                       | ¾", 1" Concentric KO                       | 1" Conduit Hub                           |
| Data Entries   | 1½" NPT Access Holes  | ¾", 1", 1¼" Concentric KO                  | 1½" Threaded Hub (included)                | 1½" Conduit Hub                          |
| Concrete Cover Included  | ✓   | ✓  | ✓  | ✓  |
| Closure Plugs Included   | ✓   | –  | ✓  | ✓  |
| Reducers   | –   | –  | –  | (see below)                              |
| Accepts Hubbell SystemOne Universal Cover  | ✓   | ✓  | ✓  | ✓  |
| Cover Mounting Clips Included  | ✓   | ✓  | ✓  | ✓  |
| Non-Metallic Low Voltage Divider Included (S1DIV1)   | ✓   | ✓  | ✓  | ✓  |

Note: UL File Number E92074.

CSA File Number LR18416.

\*S1CFB, S1SFB, S1SFBV are approved for use in the City of Chicago.

**S1PFB** reducers included: Qty (2) combo plug/reducers 1" to ¾"

Qty (2) reducers 1½" to 1"

Qty (2) reducers 1½" to ¾"

Qty (2) plugs 1½"

### SystemOne Universal Covers

- Cast aluminum construction
- Durable powder coat finish



| Color           | Carpet          | Tile            |
|-----------------|-----------------|-----------------|
| Aluminum Finish | <b>S1CFCAL</b>  | <b>S1TFCAL</b>  |
| Brass Finish    | <b>S1CFCBRS</b> | <b>S1TFCBRS</b> |
| Black           | <b>S1CFCBL</b>  | <b>S1TFCBL</b>  |
| Gray            | <b>S1CFCGY</b>  | <b>S1TFCGY</b>  |
| Ivory           | <b>S1CFCI</b>   | <b>S1TFCI</b>   |



Aluminum Finish

Brass Finish

Black

Gray

Ivory

### Floor Box Accessories

| Description   | Color         | Catalog Number                   |
|---|---------------|----------------------------------|
| <b>Abandonment Plates</b><br>Used to cover abandoned SystemOne Fire-Rated Poke-Throughs or Floor Boxes.   | Black<br>Gray | <b>S1AP4BL</b><br><b>S1AP4GY</b> |
| <b>Replacement Side by Side Divider</b><br>Used to isolate compartments in <b>S1SP</b> , <b>S1SPFFx</b> , <b>S1SPFFT</b> , <b>S1SPDU</b> , <b>S1SPDUSL</b> , <b>S1SPDU2IM</b> and <b>S1SPSL2IM</b> sub-plates. Included with all SystemOne Floor Boxes. |               | <b>S1DIV1</b>                    |
| <b>1½" Threaded Hub</b><br>For use with <b>S1SFBV</b> ONLY. Permits feed-through applications. <b>S1SFBV</b> floor box includes one (1) threaded hub.   |               | <b>S1AVHUB15</b>                 |
| <b>Replacement Universal Cover Mounting Clips</b><br>Used to mount SystemOne Universal Cover to SystemOne metal and non-metallic floor boxes ( <b>S1CFB</b> , <b>S1SFB</b> , <b>S1SFBV</b> , <b>S1PFB</b> ).  |               | <b>S1FBCLIP5PK</b>               |
| Pre-pour PVC stand increases <b>S1PFB</b> box height 2.5 in. to 4.0 in. within the concrete pour.   |               | <b>PFBSTAND</b>                  |

Dimensions in Inches (mm)



## SystemOne Flush Sub-Plates

| Description  | Catalog Number                        | Description   | Catalog Number  | Description  | Catalog Number   |
|--|---------------------------------------|---|---|--|--|
| <b>Style Line® Decorator/GFCI</b><br>(2) Style Line® decorator openings for power and/or datacom applications.   | <b>S1SP</b>                           | <b>Duplex/Duplex</b><br>(2) Duplex openings for power and/or datacom applications.  | <b>S1SPDU</b>   | <b>Duplex/Style Line® Decorator</b><br>(1) Duplex and (1) Style Line® decorator opening for power and/or datacom applications.   | <b>S1SPDUSL</b>  |
| ③ Non-Metallic ③.5 Metal   |                                       | ③ Non-Metallic ③.5 Metal  |   | ③ Non-Metallic ③.5 Metal   |  |
| <b>Hubbell 4 X 4</b><br>(4) 20A, 125V receptacles.<br>(4) Keystone openings for Hubbell jacks or flush AV connectors. Power can be wired as single or two circuit with isolated ground capability.   | <b>S1SP4X4</b>                        | <b>Carpet Furniture Feed Cover/Flange*</b><br>(1) 3/4" and (1) 1 1/2" NPT access holes for power and/or datacom applications. Universal Cover not required. Includes carpet flange. | <b>S1SPFFAL</b><br><b>S1SPFFBRS</b><br><b>S1SPFFBL</b><br><b>S1SPFFGY</b> | <b>Tile Furniture Feed Cover/Flange*</b><br>(1) 3/4" and (1) 1 1/2" NPT access holes for power and/or datacom applications. Universal Cover not required. Includes tile flange.                                    | <b>S1SPFFTAL</b><br><b>S1SPFFTBR</b><br><b>S1SPFFTBL</b><br><b>S1SPFFTGY</b> |
| ④ Includes ④ stickers.   |                                       | ③ Non-Metallic Aluminum Fin.<br>③.5 Metal Brass Finish<br>Black<br>Gray   |   | ③ Non-Metallic Aluminum Fin.<br>③.5 Metal Brass Finish<br>Black<br>Gray  |  |
| Provided with 15 ft. wire leads<br>Provided with 30 ft. wire leads   | <b>S1SP4X415</b><br><b>S1SP4X430</b>  |   |   |  |  |
| <b>Single Receptacle + Data</b><br>Opening for 20 or 30A Twist-Lock® receptacle (1.56" OD) and (2) Keystone openings for Hubbell jacks or flush AV connectors.                                       | <b>S1SPTL</b>                         | <b>Hubbell DataCom + Power</b><br>(1) 20A, 125V receptacle and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications.                                       | <b>S1SP3IM</b><br><b>S1SP3IMC</b>   | <b>Hubbell DataCom + Duplex</b><br>(1) Duplex opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications.   | <b>S1SPDU2IM</b>   |
| ④  |                                       | ⑤ Marked with "④ Controlled"  |   | ⑤  |  |
| <b>Hubbell DataCom + Style Line® Decorator</b><br>(1) Style Line® decorator opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications. | <b>S1SPSL2IM</b>                      | <b>Hubbell DataCom</b><br>1 unit flush Hubbell iSTATION opening and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications.                                  | <b>S1SP4IM</b>  | <b>Active Multimedia + Power</b><br>Single 20A, 125V receptacle; (2) flush Keystone openings; (1) rectangular Style Line® decorator opening to accommodate active multimedia modules or low voltage outlet frames. | <b>S1SPAMM20</b><br><b>S1SPAMM20C</b>  |
| ⑤  |                                       | ③.5   |   | ⑤ Marked with "④ Controlled"   |  |
| <b>Extron® or FSR + Power</b><br>(1) 20A, 125V receptacle. Recessed opening for (3) single Extron® MAAP series adapter plates or FSR IPS plates.   | <b>S1SPEXT1</b><br><b>S1SPEXT1C</b>   | <b>Extron® or FSR + Power</b><br>(1) 20A, 125V receptacle. Recessed opening for (1) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates.                 | <b>S1SPEXT2</b><br><b>S1SPEXT2C</b>                                       | <b>Extron® or FSR Single-Service</b><br>Recessed opening for (2) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates.   | <b>S1SPEXT3</b>  |
| ④ Marked with "④ Controlled"   |                                       | ④ Marked with "④ Controlled"  |   | ④.5  |  |
| <b>Extron® AAP + Power</b><br>(1) 20A, 125V receptacle. (2) flush Keystone and recessed opening for (2) single Extron® AAP Series adapter plates.  | <b>S1SPEXT4</b><br><b>S1SPEXT4C</b>   | <b>Ortronics Series II® + Power</b><br>(1) 20A, 125V receptacle. Recessed opening for (3) 1 unit Ortronics Series II® modules.  | <b>S1SPORT</b><br><b>S1SPORTC</b>   | <b>Ortronics TracJack® + Power</b><br>(1) 20A, 125V receptacle. Recessed bezel for (6) Ortronics TracJack® modules.  | <b>S1SPTRAC</b><br><b>S1SPTRACC</b>  |
| ④ Marked with "④ Controlled"   |                                       | ⑤ Marked with "④ Controlled"  |   | ⑤ Marked with "④ Controlled"   |  |
| <b>Panduit Mini Com® 4 X 4</b><br>(4) 20A, 125V receptacles.<br>(4) Openings for Panduit Mini-Com Connectivity.  | <b>S1SP4X4PA</b><br><b>S1SP4X4PAC</b> | <b>SYSTIMAX® 4 X 4</b><br>(4) 20A, 125V receptacles.<br>(4) Openings for SYSTIMAX® Connectivity.  | <b>S1SP4X4SYS</b><br><b>S1SP4X4SYSC</b>                                   | <b>Siemon MAX® + Power</b><br>(1) 20A, 125V receptacle. Recessed bezel for (6) Siemon MAX® modules.  | <b>S1SPMAX</b><br><b>S1SPMAXC</b>  |
| ④ Includes ④ stickers.   |                                       | ④ Includes ④ stickers.  |   | ⑤ Marked with "④ Controlled"   |  |

Note: \*Furnished with two screws in flexible metal conduit connectors.

③ Signifies minimum depth of concrete pour in inches for Metal Floor Boxes (**S1CFB**, **S1SFB** and **S1SFBV**) and Non-Metallic Floor Box (**S1PFB**).

## Sub-Plate Accessories

| Description   |                                   |
|---|-----------------------------------|
| <b>Replacement Threaded Conduit Plugs</b><br>Used with <b>S1SPFFx</b> and <b>S1SPFTx</b> only.<br>Sub-plate is supplied with plugs. |                                   |
| Color   | 1 1/2" Plug 3/4" Plug             |
| Aluminum Finish   | <b>S1FP15AL</b> <b>S1FP34AL</b>   |
| Brass Finish  | <b>S1FP15BRS</b> <b>S1FP34BRS</b> |
| Black   | <b>S1FP15BL</b> <b>S1FP34BL</b>   |
| Gray  | <b>S1FP15GY</b> <b>S1FP34GY</b>   |

| Description   | Catalog Number  |
|---|-----------------|
| Replacement for <b>S1SPMAX</b> . Sub-plate is supplied with data frame. Works with Siemon MAX®.                   | <b>S1DFMAX</b>  |
| Replacement for <b>S1SPTRAC</b> sub-plate. Sub-plate is supplied with data frame. Works with Ortronics TracJack®. | <b>S1DFTRAC</b> |
| Blank Style Line® decorator frame, Black.   | <b>NS620BK</b>  |
| 2-Port Style Line® decorator frame, Black.  | <b>ISF2BK</b>   |
| 4-Port Style Line® decorator frame, Black.  | <b>ISF4BK</b>   |
| 6-Port Style Line® decorator frame, Black.  | <b>ISF6BK</b>   |



Extron® is a registered trademark of Extron Electronics. MAX® is a registered trademark of The Siemon Company. Mini-Com® and Panduit® are registered trademarks of Panduit Corp. SYSTIMAX® is a registered trademark of CommScope, Inc. TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.