Aluminum Raceway





HBLALU4800 Series

es	Description	Color	Catalog Number	Description	Color	Catalog Number
4800 Serie	Two Channel Base Satin anodized finish. Packed 40 ft. (12.19m) per carton, 10 ft. (3m) lengths.	Anodized Aluminum	HBLALU4800B10 A: 2.10" (53.34) B: 6.00" (152.40)	Cover (Single Channel) Satin anodized finish. Packed 40 ft. (12.19m) per carton, 5 ft. (1.5m) lengths.	Anodized Aluminum	HBLALUC5 A: 3.00" (76.20)
HBLALU	Assembled cover and base dimensions. W: 6.00" (152.40) H: 2.25" (57.15)	A	В		A	<u></u>

					1		
		Description Internal Elbow (Two Channel)	Color Anodized	Catalog Number HBLALU4817*	Description Inverted Internal Elbow	Color Anodized	Catalog Number HBLALU4817N*
000		For making a 90° internal turn in a raceway run.	Aluminum	A: 6.00" (152.40) B: 6.00" (152.40)	(Two Channel) For connecting a vertical run of	Aluminum	A: 6.00" (152.40) B: 5.98" (151.89)
		iii a raooway run.		B. 0.00 (102.40)	HBLALU4800 with a horizontal rur	1	B. 0.00 (101.00)
			A B	•	with its cover facing up.		
						B	
	Lees	External Elbow (Two Channel)	Anodized	HBLALU4818*	Tee (Two Channel)	Anodized	HBLALU4815*
	ם	For making a 90° external turn in	Aluminum	A: 6.00" (152.40)	For branch connections of two	Aluminum	A: 9.00" (228.60)
	Elbows and Tees	a raceway run.		B: 6.00" (152.40)	runs of HBLALU4800 Raceway.		B: 9.00" (228.60)
	og		A	3			\geq
	ш		B				B
		Flat Elbow (Two Channel)	Anodized	HBLALU4811*		·	
		For making a 90° flat turn in a raceway run.	Aluminum	A: 9.00" (228.60) B: 9.00" (228.60)			
			В	7			
		No.		Í			
End Eittings		Entrance End Fitting	Anodized	HBLALU4810B2	Blank End Fitting	Anodized	HBLALU4810B
	ngs	(Two Channel) For feeding raceway, has two	Aluminum	A: 6.00" (152.40) B: 2.31" (58.74)	(Two Channel) For closing end of raceway.	Aluminum	A: 6.00" (152.40) B: 2.31" (58.74)
		concentric ½ in. and ¾ in. trade size KOs.	_	B. 2.01 (00.14)	Tor Glosing Cha of Faceway.		B. 2.01 (00.14)
	P .	trade size KOs.					
		A JB			*\\\\\\\\		
		Cover Clip To cover seam where lengths of	Stainless Steel	HBLALU4806 A: 1.38" (34.92)	Wire Clip Used for holding conductors in	Anodized Aluminum	HBLALUWC A: 1.00" (25.40)
		HBLALU4800 Raceway come together	·.	,	place on raceway. Can be used for either HBLALU3800 or		, ,
			Å	7	HBLALU4800 Raceway.		
							A
	-	Internal Corner Coupling	Anodized	HBLALU17A	Grounding Adapter	Galvanized	HBLALU09
٩	gg	For butting two raceway sections to form an internal 90° turn in a racewa	Aluminum y	A: 4.00" (101.80) B: 2.00" (50.83)	For connection of equipment grounding. #10-32 Locking	Steel	A: 4.00" (101.80) B: 2.00" (50.83)
	Fittings	run.	B		screws included.	Α -	_
Œ	ш				13		3
	-	Couplings (Pair)	Aluminum	HBLALU01		6	
		To join lengths of HBLALU3800 or	Aluminum	A: 2.85" (72.39)			
		HBLALU4800 base.	~	B: 4.00" (101.80)			
			/. //				
NIC	o t o *	*HBI AI U01 couplings included.					

Note: *HBLALU01 couplings included. See page R-40 for cover plates.

Dimensions in Inches (mm)