

**30 Amp, 3ØY 120/208, 277/480 and 347/600 Volts AC  
4 Pole, 4 Wire, Non-Grounding**

**IP20**  
SUITABILITY



30A 3ØY 120/208V AC  
NEMA L18-30P  
3 HP

30A 3ØY 277/480V AC  
NEMA L19-30P  
10 HP

30A 3ØY 347/600V AC  
NEMA L20-30P

## Plugs

| Description            | Cord Dia.              | Catalog Number                               |
|------------------------|------------------------|----------------------------------------------|
| Black and white nylon. | .350"-1.150"<br>(9-29) | <b>HBL2751</b> <b>HBL2761</b> <b>HBL2771</b> |

Note: See page B-55 for accessories.

## Flanged Inlets

| Description               | Catalog Number                               |
|---------------------------|----------------------------------------------|
| Nylon casing, back wired. | <b>HBL2755</b> <b>HBL2765</b> <b>HBL2775</b> |

Note: See page B-54 for accessories.

**IP20**  
SUITABILITY



30A 3ØY 120/208V AC  
NEMA L18-30R  
3 HP

30A 3ØY 277/480V AC  
NEMA L19-30R  
10 HP

30A 3ØY 347/600V AC  
NEMA L20-30R

## Connector Bodies

| Description            | Cord Dia.              | Catalog Number                               |
|------------------------|------------------------|----------------------------------------------|
| Black and white nylon. | .350"-1.150"<br>(9-29) | <b>HBL2753</b> <b>HBL2763</b> <b>HBL2773</b> |

Note: See page B-54 for accessories.

## Single Flush Receptacles

| Description                            | Catalog Number                               |
|----------------------------------------|----------------------------------------------|
| Black nylon face, back and side wired. | <b>HBL2750</b> <b>HBL2760</b> <b>HBL2770</b> |

Note: See page B-54 for accessories.

## Flanged Receptacles


| Description               | Catalog Number                               |
|---------------------------|----------------------------------------------|
| Nylon casing, back wired. | <b>HBL2756</b> <b>HBL2766</b> <b>HBL2776</b> |

Note: See page B-54 for accessories.

See page B-71 for technical information on Twist-Lock devices.




**HBL2751**




**HBL2755**



**HBL2753**



**HBL2750**



**HBL2756**

Dimensions in Inches (mm)

## Brass Locking Cover Plate

| Description                                                                                                                                                           | Catalog Number  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| Locking cover plate for single 15 and 20A straight blade receptacles and 15A Twist-Lock® receptacles.<br>Straight cylinder type lock. All cylinder locks keyed alike. | <b>HBL96067</b> |



**HBL96067**  
Shown with receptacle  
(sold separately)



**HBL6187**  
Shown with receptacle  
and back box  
(sold separately)

## Weather Shield Wallplate

| Description                                 | Catalog Number |
|---------------------------------------------|----------------|
| 20° angle wallplate for duplex receptacles. | <b>HBL6187</b> |

## Catalog Number of Receptacles in Groups A through E below

| Group A                                           |                  | Group B                                           |                  |                  | Group C                                           | Group D                                           |                                                       | Group E                                           |
|---------------------------------------------------|------------------|---------------------------------------------------|------------------|------------------|---------------------------------------------------|---------------------------------------------------|-------------------------------------------------------|---------------------------------------------------|
| Boss diameter<br>1.36" to 1.39"<br>(34.5 to 35.3) |                  | Boss diameter<br>1.55" to 1.58"<br>(39.4 to 40.1) |                  |                  | Boss diameter<br>1.68" to 1.72"<br>(42.7 to 43.7) | Boss diameter<br>2.09" to 2.13"<br>(53.1 to 54.1) |                                                       | Boss diameter<br>2.28" to 2.44"<br>(57.9 to 62.0) |
| <b>HBL23000HG</b>                                 | <b>HBL5661</b>   | <b>HBL23CM10</b>                                  | <b>HBL2530</b>   | <b>HBL2770</b>   | <b>HBL45105</b>                                   | <b>HBL7962</b>                                    | <b>HBL9360•</b><br><b>HBL9365•</b><br><b>HBL9367•</b> | <b>HBL7301A</b>                                   |
| <b>HBL23030</b>                                   | <b>HBL6810</b>   | <b>HBL2310</b>                                    | <b>HBL26CM10</b> | <b>HBL2810</b>   | <b>HBL45205</b>                                   | <b>HBL9350</b>                                    |                                                       | <b>HBL8330A</b>                                   |
| <b>HBL4560</b>                                    | <b>HBL7210B</b>  | <b>HBL2320</b>                                    | <b>HBL2610</b>   | <b>HBL2820</b>   | <b>HBL45305</b>                                   | <b>HBL9308</b>                                    |                                                       | <b>HBL8350A</b>                                   |
| <b>HBL4710</b>                                    | <b>HBL7250</b>   | <b>HBL2330</b>                                    | <b>HBL2620</b>   | <b>HBL2830</b>   | <b>HBL45905</b>                                   | <b>HBL9315</b>                                    |                                                       | <b>HBL8430A</b>                                   |
| <b>HBL4760</b>                                    | <b>HBL7310B</b>  | <b>HBL2340</b>                                    | <b>HBL2630</b>   | <b>HBL3330</b>   |                                                   | <b>HBL9330</b>                                    |                                                       | <b>HBL8450A</b>                                   |
| <b>HBL5251</b>                                    | <b>HBL7310BG</b> | <b>HBL2410</b>                                    | <b>HBL2640</b>   | <b>HBL3330G</b>  |                                                   | <b>HBL9360•</b>                                   |                                                       | <b>HBL8460A</b>                                   |
| <b>HBL52CM61</b>                                  | <b>HBL7535</b>   | <b>HBL2420</b>                                    | <b>HBL2650</b>   | <b>HBL3430</b>   |                                                   | <b>HBL9365•</b>                                   |                                                       | <b>HBL9430A</b>                                   |
| <b>HBL5261</b>                                    | <b>HBL7582</b>   | <b>HBL2430</b>                                    | <b>HBL2710</b>   | <b>HBL3430G</b>  |                                                   | <b>HBL9367•</b>                                   |                                                       | <b>HBL9450A</b>                                   |
| <b>HBL53CM61</b>                                  | <b>HBL8210</b>   | <b>HBL2440</b>                                    | <b>HBL2720</b>   | <b>HBL3520</b>   |                                                   |                                                   |                                                       | <b>HBL9460A</b>                                   |
| <b>HBL5361</b>                                    | <b>HBL8310</b>   | <b>HBL2450</b>                                    | <b>HBL2730</b>   | <b>HBL7410B</b>  |                                                   |                                                   |                                                       |                                                   |
| <b>HBL5461</b>                                    | <b>HBL8410</b>   | <b>HBL2460</b>                                    | <b>HBL2740</b>   | <b>HBL7410BG</b> |                                                   |                                                   |                                                       |                                                   |
| <b>HBL5552B</b>                                   | <b>HBL8420</b>   | <b>HBL2510</b>                                    | <b>HBL2750</b>   |                  |                                                   |                                                   |                                                       |                                                   |
|                                                   |                  | <b>HBL2520</b>                                    | <b>HBL2760</b>   |                  |                                                   |                                                   |                                                       |                                                   |

Note: •50A 2P 3W.

## Wallplates for Single Receptacles

| Description                          | Group A                                           |             | Group B                                           |        | Group C                                           |        | Group D                                           |               | Group E                                           |
|--------------------------------------|---------------------------------------------------|-------------|---------------------------------------------------|--------|---------------------------------------------------|--------|---------------------------------------------------|---------------|---------------------------------------------------|
|                                      | Boss diameter<br>1.36" to 1.39"<br>(34.5 to 35.3) |             | Boss diameter<br>1.55" to 1.58"<br>(39.4 to 40.1) |        | Boss diameter<br>1.68" to 1.72"<br>(42.7 to 43.7) |        | Boss diameter<br>2.09" to 2.13"<br>(53.1 to 54.1) |               | Boss diameter<br>2.28" to 2.44"<br>(57.9 to 62.0) |
|                                      | 1-Gang                                            | 2-Gang      | 1-Gang                                            | 2-Gang | 1-Gang                                            | 2-Gang | 1-Gang                                            | 2-Gang        | 2-Gang                                            |
| Smooth nylon, brown.                 | <b>NP7*</b>                                       | –           | <b>NP720*</b>                                     | –      | –                                                 | –      | <b>NP724*</b>                                     | <b>NP703*</b> | –                                                 |
| Cast aluminum.                       | <b>HBL7320</b>                                    | –           | <b>HBL7320</b>                                    | –      | <b>HBL3394</b>                                    | –      | <b>HBL9419</b>                                    | –             | –                                                 |
| Stainless steel,<br>302/304, smooth. | <b>SS7**</b>                                      | <b>SS72</b> | <b>SS720</b>                                      | –      | <b>SS725</b>                                      | –      | <b>SS723</b>                                      | <b>SS703</b>  | <b>SS701</b>                                      |

Note: See pages O-7 and O-8 for complete wallplate descriptions.

\*Catalog number indicated is Brown, add with the following to designate color: "AL" (Almond), "BK" (Black), "GY" (Gray), "I" (Ivory), and "W" (white).

\*\*Catalog number indicated is Stainless Steel, replace "SS" with the following prefix to designate material: "SA" for Anodized Aluminum, "SB" for Solid Brass.

## Weatherproof Lift Covers for WDL "Closed" and WDL "Open", Wet Locations, 1-Gang

| Description                                  | Group A                                           | Group B                                           | Group C                                           | Group D                                           | 50A<br>Twist-Lock®<br>Receptacles |  | 30A 4W<br>Hubbellock®<br>Receptacles |
|----------------------------------------------|---------------------------------------------------|---------------------------------------------------|---------------------------------------------------|---------------------------------------------------|-----------------------------------|--|--------------------------------------|
|                                              | Boss diameter<br>1.36" to 1.39"<br>(34.5 to 35.3) | Boss diameter<br>1.55" to 1.58"<br>(39.4 to 40.1) | Boss diameter<br>1.68" to 1.72"<br>(42.7 to 43.7) | Boss diameter<br>2.09" to 2.13"<br>(53.1 to 54.1) |                                   |  |                                      |
| Thermoplastic, with<br>cover "open", gray.   | <b>HBL7423WO</b>                                  | <b>HBL7425WOA</b>                                 | <b>HBL7424WO</b>                                  | –                                                 | <b>HBL7774WO▲</b>                 |  | –                                    |
| Thermoplastic, with<br>cover "open", yellow. | <b>HBL74CM23WO</b>                                | <b>HBL74CM25WOA</b>                               | <b>HBL74CM24WO</b>                                | –                                                 | <b>HBL77CM74WO▲</b>               |  | –                                    |
| Cast aluminum, with<br>cover "closed".       | <b>HBL7420</b>                                    | <b>HBL7420</b>                                    | <b>HBL3393</b>                                    | <b>HBL9420</b><br><b>HBL9425•</b>                 | <b>HBL7770</b>                    |  | <b>HBL20405†</b><br><b>HBL20446†</b> |

Note: •50A 2P 3W.

▲The "CS" versions of 50A Twist-Lock® receptacles will only fit these thermoplastic wallplates.

†HBL20446 wallplate painted red for use with HBL20443 only. HBL20405 wallplate is for use with HBL20403 only. See page B-65 for devices.