Thomas@Betts





ATC 1250 R 750


UPC Number: 78378669710

Status: Active

Description:

Aluminum Tapered Reducing Splices, wire size 750-1250

Features	
	Solid Center Stop assures proper cable insertion.
	Joild Certier Gtop assures proper cable insertion.
	Dual-Rated. Use with aluminum and copper con-
	ductors.
	Connector bores coated with Oxide Inhibitor to pre-
	vent oxidation.
	All splices marked with conductor sizes, and die ref
	erences for easy identification.
	Tapered ends enable use in high-voltage applica-
	tions up to 69kV.
General	
Style	Aluminum Splices
Material	Aluminum



	Tapered ends enable use in high-voltage applica-
	tions up to 69kV.
General	
Style	Aluminum Splices
	·
Material	Aluminum
Wire Size (min)	750
Wire Size (max)	1250
Dimension Information	
B (inches)	4 3/8
L (inches)	9 7/8
Tooling	
Installing Dies	302,161,292,319,727
Notes	
	For tin-plating option, add '-TN' suffix to the catalog number.
Certifications	

Certifications
Standards Compliant Meets or exceeds ANSI C119.4 specifications.

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com