

SETRON, Fuse switch disconnecter 3NP5, 3-pole, NH00, 160 A, for assembly and installation on mounting plate, with High-speed closing, Clamp terminal



Figure similar

Model	
Product brand name	SETRON
Product designation	3NP5 fuse switch disconnecter
Design type	For assembly and installation, with high-speed closing
Design of the operating mechanism	Cover handle
Design of the load switch / Strip form	No
General technical data	
Number of poles	3
Size of disconnecting link	NH000, NH00
Size of fuse link	NH000, NH00
Continuous current / at 35 °C / rated value	160 A
power factor cos phi / in utilization category	
• AC-21 B / at 400 V	0.95
• AC-21 B / at 500 V	0.95
• AC-22 B / at 400 V	0.65
• AC-22 B / at 500 V	0.65
circuit-breaker / Design	3NP506

Mounting type	Fixed mounting
Fuse system	LV HRC fuse
Voltage	
Type of voltage	AC/DC
Insulation voltage / rated value	690 V
Surge voltage resistance / rated value	6 kV
Protection class	
Protection class IP / on the front	IP00
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	2.66 W
Electricity	
Current / rated value	160 A
Continuous current	
• rated value	160 A
• at 40 °C / rated value	157 A
• at 45 °C / rated value	154 A
• at 50 °C / rated value	147 A
• at 55 °C / rated value	141 A
• at 60 °C / rated value	133 A
• at 65 °C / rated value	136 A
• at 70 °C / rated value	117 A
Let-through current / I_{2t} / maximum permissible / in utilization category	
• AC-21 B / at 400 V	225 000 A ² ·s
• AC-21 B / at 500 V	225 000 A ² ·s
• AC-22 B / at 400 V	225 000 A ² ·s
• AC-22 B / at 500 V	225 000 A ² ·s
Let-through current / I_c / maximum permissible / in utilization category	
• AC-21 B / at 400 V	15 kA
• AC-21 B / at 500 V	15 kA
• AC-22 B / at 400 V	15 kA
• AC-22 B / at 500 V	15 kA
Main circuit	
Operating voltage	
• at AC / at 50/60 Hz / rated value	690 V
• at AC / rated value / maximum	690 V
• at DC / rated value	440 V
Rated current I_e / maximum / in utilization category	
• AC-21 B / at 400 V	160 A

• AC-21 B / at 500 V	160 A
• AC-22 B / at 400 V	160 A
• AC-22 B / at 500 V	160 A

Suitability

Suitability for use	system protection
• Main switch	No
• switch disconnector	Yes
• EMERGENCY OFF switch	No
• safety switch	Yes

Product function

Product function / fuse monitoring	No
------------------------------------	----

Short circuit

Maximum short-circuit current breaking capacity (Icu) / at 400 V / rated value	1.6 kA
Conditional rated short-circuit current / in utilization category	
• AC-21 B / at 400 V	50 kA
• AC-21 B / at 500 V	50 kA
• AC-22 B / at 400 V	50 kA
• AC-22 B / at 500 V	50 kA

Connections

Type of electrical connection	1 conductor 2.5 - 50 mm ² , 2 conductors 1x2.5 - 50 mm ² a. 1x2.5 - 35 mm ²
• for main current circuit	terminal clamp

Mechanical Design

Height	196 mm
Width	134 mm
Depth	97.5 mm
Number of width units	1
Mounting type	Mounting plate
Mounting type	
• floor mounting	Yes
• front mounting	No
• rail mounting	No
Net weight	1 733 g

Environmental conditions

Degree of pollution	3
Installation altitude / at height above sea level / maximum	2 000 m
Ambient temperature	

- during operation / minimum -25 °C
- during operation / maximum 55 °C
- during storage / minimum -50 °C
- during storage / maximum 80 °C

Certificates

Reference code

- acc. to DIN EN 61346-2 Q
- acc. to DIN EN 81346-2 Q

General Product Approval	Declaration of Conformity	Test Certificates	other	
 CCC	 EG-Konf.	Special Test Certificate	Miscellaneous	Confirmation

[Miscellaneous](#)

[Special Test Certificate](#)

[Miscellaneous](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NP5060-0CB00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NP5060-0CB00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NP5060-0CB00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



