



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

**Search Parameters:**

[e-Catalog](#) > [Switches & Disconnects](#) > [Disconnect & Safety Switches](#)

**Switches & Disconnects, Disconnect & Safety Switches**

Product #: THN3362SS

Short Description: 60A 3P HD SS N4X 600V NONFUSE

[Print This Page](#)

[Email This Page](#)

**SPECIFICATIONS**

Category	Heavy Duty
Voltage	600 AC
Amperage	60 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 4/4X Water/Dust-tight
Options	None
Notes	Order THN3362SS-BA for ARRA compliance
Height	19.33 in
Depth	5.44 in
Width	9.39 in
Weight	21.0 lb
Wire Range (Cu/Al)	12-2
240 Vac, NEC Std, 1-ph	10 hp
240 Vac, NEC Std, 3-ph	20 hp
125 Vdc	5 hp
250 Vdc	10 hp
GSA Compliance	Yes
CSA Certified	Yes
UL Listed	Yes
GO Schedule	131
List Price	\$1577



[View Larger](#)

**Publications/Resources**

[THN3362SS](#)

**Additional Resources for Heavy Duty**

[Application and Technical](#)

[Brochures](#)

[Drawings-Outline and Dimensional](#)

[BIM Files](#)

[Buy Log :2-12](#)

- Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type HD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism.
- 60/75°C conductor rating.
- Full cover interlocks.
- NEMA type 4X enclosure grade 304 stainless steel (catalog numbers with SS suffix).

