



TRANSFORMER SITAS; PHASES:1;  
 PN/PN(S6)(KVA):1,6 /7,3; UPRI(V):400+/-5%;  
 USEC(V):230; ISEC(A):6,96; F(HZ):50...60; VECTOR  
 GR./SHIELD WNG.:II0 /0; TA/ISOKL:40 /B; IP00; TYPE  
 OF TERMINALS:SCREW/TAB CONNECTION;  
 INSTALLATION:SCREW; EN 61558-2-1, -2-2, -2-4  
 >UL/CSA-RECOGNIZED< >CONTROL CIRCUIT  
 TRANSFORMER< >ISOLATION TRANSFORMER<

Figure similar

General technical data		
Product designation		transformer SITAS
Product brand name		SIDAC
Operating apparent output rated value	V·A	1 600
Efficiency		0.96
Connection method for transformers		II0
Certificate of suitability		CE / cRUus
Product function		
• Temperature monitoring		No
• Insulation monitoring		No
• Short-circuit and overload proof		No
Number of shielding windings		0
Short-term vector power	V·A	7 300
Relative short-circuit voltage	%	2.5
Inputs		
Phase number of the inputs		1
Input voltage		

• _1 rated value	V	420
• _2 rated value	V	400
• _3 rated value	V	380
<b>Electrical input frequency</b>		
• minimum	Hz	50
• maximum	Hz	60

### Outputs

<b>Phase number of the outputs</b>		1
<b>Output voltage</b>		
• _1 rated value	V	230
<b>Electrical output frequency</b>		
• maximum	Hz	60
• minimum	Hz	50

### Ambient conditions

<b>Thermal class acc. to IEC 60085</b>		B
<b>Ambient temperature rated value</b>	°C	40
<b>Protection class IP</b>		IP00

### Mechanical data

<b>Type of electrical connection</b>		
• at output for main current circuit		screw-type terminals / tab terminals
• at input for main current circuit		screw-type terminals / tab terminals
<b>Mounting type</b>		screws
<b>Construction form of the iron core</b>		EI 174/82
<b>Width</b>	m	0.176
<b>Height</b>	m	0.164
<b>Depth</b>	m	0.138

### Certificates/ approvals

General Product Approval	Declaration of Conformity	Shipping Approval	other
--------------------------	---------------------------	-------------------	-------



[Miscellaneous](#)



[Confirmation](#)

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AM6142-5AT10-0FA0>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4AM6142-5AT10-0FA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/4AM6142-5AT10-0FA0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=4AM6142-5AT10-0FA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4AM6142-5AT10-0FA0&lang=en)

**last modified:**

02/26/2020