

## Eaton heavy duty DC disconnect

DCU3063UPM

UPC:786685557502

### Dimensions:

- **Height:** 24.95 IN
- **Length:** 10.22 IN
- **Width:** 16.13 IN

**Weight:**30 LB

**Notes:**Not all configurations for ampere rating and number of circuits are available. All circuit configurations can be found in the product dimension tables.

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Type:** DC disconnect/ungrounded system
- **Amperage Rating:** 100A
- **Application:** Solar
- **Enclosure:** NEMA 4
- **Enclosure Material:** Painted steel
- **Fuse Configuration:** Non-fusible
- **Ground:** Ungrounded
- **Main Lug Wire Size:** #14-1/0 AWG lug capacity, #14-1/0 AWG solid return
- **Maximum Voltage:** 600 Vdc
- **Number Of Circuits:** 3
- **Series:** DC Photovoltaic Applications
- **Switch Type:** Heavy-duty
- **System Voltage:** 600 Vdc per pole

### Supporting documents:

- [DC disconnects for grounded and ungrounded](#)

photovoltaic installations

- Eaton's Volume 15-Solar Inverters and Electrical Balance of System
- Eaton Specification Sheet - DCU3063UPM

**Certifications:**

- NEC 690 per UL 1741
- UL 98B

**Product compliance:** No Data

---

© 2016 Eaton. All rights reserved.