

## Eaton K-Factor nonlinear ventilated transformer

**HT29M11S2516CU**

**UPC:**786680207174

**Dimensions:**

- **Height:** 37.59 IN
- **Length:** 20.36 IN
- **Width:** 22.87 IN

**Weight:**437 LB

**Notes:**DOE 2016 Efficient

**Warranties:**

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

**Specifications:**

- **Special Features:** Electrostatically shielded
- **Type:** Nonlinear, ventilated transformer
- **Coil Material:** Copper
- **Enclosure:** NEMA 2
- **Frame:** 818
- **Frequency Rating:** 60 Hz
- **Phase:** Single-phase
- **Primary Voltage:** 208 V
- **Secondary Voltage:** 120/240 V
- **Tap Size:** 2 at +2.5% FCAN, 4 at -2.5% FCBN
- **Temperature Rise:** 150 °C rise
- **Volt Ampere Rating:** 25 kVA
- **Weathershield:** WS11
- **Wiring Connection:** 264A

**Supporting documents:**

- [Eaton Specification Sheet - HT29M11S2516CU](#)

**Certifications:**

- UL Listed



**Product compliance:** No Data

---

© 2016 Eaton. All rights reserved.