



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## SRT2 series Sag ride through

**SRT20750480AA**

**UPC:**786685179445

### Dimensions:

- **Height:** 85 IN
- **Length:** 64 IN
- **Width:** 32 IN

**Weight:**4185 LB

**Notes:**Contact Product Line for Price and Availability

### Warranties:

- 1 year

### Specifications:

- **Frequency Rating:** 60 Hz
- **Phase:** Three-Phase
- **Type:** Sag ride through
- **Voltage Rating:** 480V
- **Breaking Capacity:** 40000 KVA
- **Correction:** 40% (+10/-40%)
- **Dissipation Factor:** 12.2 kW
- **Efficiency:** 98.44%
- **Load Capacity:** 750000 KVA
- **Number Of Wires:** Three-wire
- **Humidity:** <95% noncondensing
- **Volt Ampere Rating:** 750 kVA

### Supporting documents:

- [Eatons Volume 3-Power Distribution and Control Assemblies](#)
- [Sag ride through device for providing facility uptime](#)
- [Eaton Specification Sheet - SRT20750480AA](#)

### Certifications:

- Semi-F47 Certified



**Product compliance:** No Data

---

© 2016 Eaton. All rights reserved.