



Figure similar

Product brand name	Control Power Transformer
Design of the product	Control power voltage
Special product feature	Touch safe terminals

General technical data	
Weight [lb]	13.6 lb
Height x Width x Depth [in]	3.82 × 4.5 × 5.19 in
Ambient temperature [°F]	-4 ... +104 °F
<ul style="list-style-type: none"> <li>during operation</li> </ul>	
Ambient temperature	-20 ... +40 °C
<ul style="list-style-type: none"> <li>during operation</li> </ul>	
Country of origin	Mexico
Operating apparent output rated value	350 V·A

Enclosure	
Design of the housing	Open

Mounting/wiring	
Mounting position	Any
Mounting type	Surface mounting

Type of electrical connection at output for main current circuit	Screw-type terminals (touchsafe)
Type of electrical connection at input for main current circuit	Screw-type terminals (touchsafe)

Inputs/ Outputs	
Input dimensions of primary voltage	380vac
Output dimensions of secondary voltage	24vac
Phase number of the inputs	1
Electrical input frequency	50 ... 60 Hz
Input voltage _1	380 V
Phase number of the outputs	1
Electrical output frequency	60 ... 50 Hz
Output voltage _1 rated value	24 V
Certificate of suitability	UL / CSA

#### Further information

**Industrial Controls - Product Overview (Catalogs, Brochures,...)**

[www.usa.siemens.com/iccatalog](http://www.usa.siemens.com/iccatalog)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mfb=US2:MTG0350P>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/US/en/ps/US2:MTG0350P>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=US2:MTG0350P&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=US2:MTG0350P&lang=en)

**Certificates/approvals**

<https://support.industry.siemens.com/cs/US/en/ps/US2:MTG0350P/certificate>

**last modified:** 11/15/2019