

### Product type designation

### Power Supply SCALANCE PS9230 PoE

SCALANCE PS924 PoE power supply for Power-over-Ethernet,  
Input: 24 V DC output: 54 V DC/1.6 A NEC Class 2



Type of current supply	Input: DC 24 V, Output: DC 54 V / 1.6 A, NEC CLASS 2
Suitability for use	Power supply for PoE

Electrical data / Input	
Voltage curve / at input	DC
Supply voltage / Rated value	24 V
Supply voltage / rated value	19.2 ... 28.8 V
Type of voltage / of the supply voltage	DC
Consumed current / at rated supply voltage / maximum	4.1 A
Design of input / wide range input	No
Buffering time / for rated value of the output current / in the event of power failure / minimum	5 ms
Current limitation / of inrush current / at 25 °C / maximum	10 A
Fuse protection type / at input	Fuse T 15A soldered

Electrical data / Output	
Voltage curve / at output	Controlled, isolated DC voltage, adjustable from 48 V to 54 V
Output voltage / at DC / Rated value	54 V

Display version / for normal operation	LED green for DC ok
Behavior of the output voltage / when switching on	Overshoot of $U_a < 2 \%$
ON-delay time / maximum	1.5 s
Voltage increase time / of the output voltage / maximum	15 ms
Output current	
• Rated value	1.6 A
• Rated range	0 ... 1.8 A
Supplied active power / typical	86 W
Product feature / Parallel switching of channels	No
Number of parallel-switched resources / for increasing the power	0
Efficiency in percent	86 %
Power loss [W]	14 W

#### Electrical data / closed-loop control

Relative overall tolerance / of the voltage	1 %
Residual ripple / maximum	0.05 V
Voltage peak / maximum	0.2 V
Relative control precision / of the output voltage	
• On slow fluctuation of input voltage	0.2 %
• On slow fluctuation of ohm loading	0.5 %
• load step of resistive load 50/100/50 % / typical	0.5 %
• with rapid fluctuation of the input voltage by +/- 15% / typical	0.3 %
Setting time	
• load step 50 to 100% / typical	0.5 ms
• load step 100 to 50% / typical	0.5 ms

#### Electrical data / protection and monitoring

Design of the overvoltage protection / at output	< 60 V
Response value current limitation / typical	1.7 A
Property of the output / Short-circuit proof	Yes
Design of short-circuit protection	Electronic shutdown, automatic restart

#### Electrical data / safety

Galvanic isolation / between entrance and outlet	Yes
Galvanic isolation	Safety extra-low output voltage $U_{out}$ acc. to EN 60950-1
Operating resource protection class	Class III
Leakage current	
• maximum	3.5 mA
• typical	0 mA

#### Interfaces

Number of electrical connections	
• for power supply	3

<ul style="list-style-type: none"> <li>• for signaling contact</li> </ul>	2
Type of electrical connection	
<ul style="list-style-type: none"> <li>• for signaling contact</li> <li>• at input</li> <li>• at output</li> </ul>	Screw terminal 0.5 - 2.5 mm <sup>2</sup> FE / + / - screw-type terminal 0,5 - 2,5 mm <sup>2</sup> 2x + / 2x - , screw-type terminal 0.5 - 2.5 mm <sup>2</sup>

### Signal inputs/outputs

Product component / Signaling contact	Yes
Relay design	Normal open contact (N/O)
Operating voltage / of the signaling contacts	
<ul style="list-style-type: none"> <li>• at DC / Rated value</li> <li>• at DC / maximum</li> </ul>	24 V 60 V
Operating current / of the signaling contacts	
<ul style="list-style-type: none"> <li>• at DC / maximum</li> <li>• at DC / at 30 V / maximum</li> </ul>	0.3 A 0.3 A
Width	42 mm
Height	125 mm
Depth	125 mm
Net weight	0.5 kg
Product feature / of the enclosure / housing for side-by-side mounting	Yes
Mounting type	
<ul style="list-style-type: none"> <li>• 19-inch installation</li> <li>• wall mounting</li> <li>• 35 mm DIN rail mounting</li> <li>• S7-300 rail mounting</li> </ul>	No No Yes No

### Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage</li> <li>• during transport</li> <li>• Note</li> </ul>	-40 ... +70 °C -40 ... +85 °C -40 ... +85 °C Convection
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Environmental category / acc. to IEC 60721	Climate class 3K3, without condensation
Protection class IP	IP20

### Standards, specifications, approvals

Standard	
<ul style="list-style-type: none"> <li>• for safety / from CSA and UL</li> <li>• for emitted interference</li> <li>• for interference immunity</li> </ul>	cULus listed (UL508, CSA C22.2 No. 107.1) EN 61000-6-4: 2007 EN 61000-6-2
Certificate of suitability	EN 61000-6-4: 2007

- CE marking
- C-Tick

Yes

Yes

## Further information / Internet-Links

### Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

**last modified:**

11/19/2019