

Product type designation
Product description

Cable RS422, wire end sleeves / EN 175201-804 straight
Highly flexible communication line (6-core)
MOBY I/E/U plug-in cable ASM 470/475-SLG straight SLG
connector, PUR, trailing, length 2 m



Suitability for use	Plug-in cable for connecting a MOBY U SLG to the communication module ASM 475
Cable designation	L-YC11Y 6x1x0.25 6x24AWG CM
Wire length	2 m

Electrical data	
Number of electrical connections	1
Type of electrical connection	wire end sleeves (labeled) / EN 175201-804 (female, 7 pin, straight)
Loop resistance per length / maximum	160 mΩ/m
Insulation resistance coefficient	20 GΩ·m
Operating voltage	
• maximum	300 V

Mechanical data	
Number of electrical cores	6
Design of the shield	Braided shield made of tin-plated copper wires
Outer diameter	
• of cable sheath	5.4 mm

Symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
Material	
<ul style="list-style-type: none"> • of the wire insulation • of cable sheath 	PVC PUR
Color	
<ul style="list-style-type: none"> • of the insulation of data wires • of cable sheath 	DIN 47100 Black
Bending radius	
<ul style="list-style-type: none"> • with single bend / minimum permissible • with multiple bends / minimum permissible • with continuous bending 	21.6 mm 43 mm 75 mm
Number of bending cycles	3000000
Tensile load / maximum	200 N
Weight per length	45 kg/km

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport • during installation 	-30 ... +80 °C -30 ... +80 °C -30 ... +80 °C -30 ... +80 °C
Burning behavior	flame resistant according to IEC 60332-1-2
Chemical resistance	
<ul style="list-style-type: none"> • to mineral oil • to grease 	resistant resistant
Radiological resistance / to UV radiation	resistant

Product features, product functions, product components / general

Product feature	
<ul style="list-style-type: none"> • halogen-free • silicon-free 	No Yes

Standards, specifications, approvals

UL/ETL listing / 300 V Rating	Yes; CM (only cable without plug)
-------------------------------	-----------------------------------

Further information / Internet-Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager 	https://support.industry.siemens.com/cs/ww/en/view/67384964 http://www.siemens.com/ident/rfid https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax

- to website: Industry Online Support

<https://support.industry.siemens.com>

last modified:

10/26/2019