

Insulating and Splicing – Rubber Tapes

Scotch® Varnished Cambric Tape 2520

Scotch® Varnished Cambric Tape 2520 is made from straight-cut woven cotton cambric fabric. The fabric is oil primed and coated with a high-grade yellow electrical insulating varnish. Varnished cambric tapes are flexible, electrically insulating and moisture resistant with a smooth finish. Scotch Tape 2520 tape is yellow with a pressure-sensitive adhesive and 8 mils thick, and contains an adhesive that holds the tape in position after application. It is designed to perform continuously in temperatures up to 105°C (220°F) with excellent resistance to abrasion, puncture and cut-through.

Material	Straight cut woven cotton cambric with electrical insulating varnish
Tape Grade	Premium
Tape Type	Insulating and Splicing
Operating Temperature	Up to 220°F (105°C)
RoHS 2011/65/EU	Yes
Specifications	ASTM D-374; ASTM D-1000; ASTM D-295
Country of Origin	Pakistan



Order No.	UPC	Color	Length	Width	Thickness	Breaking Strength	Rolls per Carton	Rolls per Case
2520-3/4X60FT	054007-04836	Yellow	60'	0.75"	8 mil	50 lbs/in	1	20
2520-3/4X36YD	054007-04835	Yellow	36 yd	0.75"	8 mil	50 lbs/in	1	48
2520-1X36YD	054007-04833	Yellow	36 yd	1.00"	8 mil	50 lbs/in	1	36
2520-1-1/2X36YD	054007-04832	Yellow	36 yd	1.50"	8 mil	50 lbs/in	1	24
2520-2X36YD	054007-04834	Yellow	36 yd	2.00"	8 mil	50 lbs/in	1	16

Scotch® Electrical Shielding Tape 24

Scotch® Electrical Shielding Tape 24 is an all-metal, flat, open-weave shielding mesh that is compatible with power cable insulations and all high-voltage splicing and terminating materials. Scotch® Electrical Shielding Tape 24 elongates easily to conform and is temperature stable.

NOTE: Scotch® Electrical Shielding Tape 24 should not be used as a ground strap or jumper wire. It's ampacity is not great enough to carry large fault currents. For ground strap applications please refer to Scotch® Electrical Grounding Braid 25.

Material	Tinned Copper Open Weave Mesh
Tape Grade	Premium
Tape Type	Shielding
RoHS 2011/65/EU	Yes
Country of Origin	Mexico



Order No.	UPC	Length	Width	Thickness	Breaking Strength	Rolls per Carton	Rolls per Case
24-1X100FT	054007-15058	100'	1.00"	16 mil	22 lbs/in	10	10
24-1X15FT	054007-15041	15'	1.00"	16 mil	22 lbs/in	10	50
24-2X10FT	051128-57289	10'	2.00"	16 mil	22 lbs/in	20	20