



The Juno® WarmDim® LED Family



600 and 900 Lumen LED Downlights

Juno LED IC-rated downlights with the WarmDim feature are available with 600 or 900 brilliant lumens, and new construction or remodel housings. Aperture sizes include 4-, 5-, and 6-inch diameters and are offered with open, lensed, and wall wash trims. These ultra-efficient downlights consume as little as 12 watts, producing industry-leading efficacies for their category.



600 Lumen Retrofit LED Trim Modules

Juno LED retrofit modules with the WarmDim feature produce 600 brilliant lumens and are available with downlight or adjustable eyeball trims. This is the fast, affordable way to update existing fixtures to ultra-efficient, high-performance LED illumination. They are compatible with most 6-inch medium base housings and offer an all-in-one design that is the model of installation simplicity.



900 Lumen Slope Ceiling LED Downlights

Juno slope ceiling LED downlights with the WarmDim feature are designed specifically for sloped ceiling applications. They are available in either standard or super slope configurations and produce a brilliant 900 lumens to accommodate higher ceilings. These ultra-efficient, IC-rated, 6-inch LED luminaires are the perfect complement to today's contemporary decors.



Juno 6" WarmDim Downlights (New Construction)



Dedicated LED, Air-Loc® sealed new construction housing with patented WarmDim®. LED color temperature warms while dimming to emulate the dimming performance of traditional incandescent light sources. Shallow housing allows for fit in 2 x 6 construction. Can be completely covered with insulation. Fully sealed housing stops infiltration and exfiltration of air, reducing heating and air cooling costs without the use of additional gaskets. LED housing is designed to provide 50,000 hours of life and is compatible with many standard Juno trims. 5 year limited warranty on LED components.

New Construction

15 1/4" L x 9 1/4" W x 5 1/2" H
Ceiling cutout: 6 7/8"

Example: IC22LED WD G4N 06LM 30K 90CRI 120 FRPC

Series	Dynamic Feature	Gen	Lumens	CCT	CRI	Voltage/Driver
IC22LED 6" New Construction Housing	WD WarmDim®	G4N	06LM 600 Lumens	30K 3000K	90CRI	120 FRPC 120V Only; Forward Phase/ ELV Dimming
		G4	09LM 900 Lumens			

Juno 6" WarmDim Downlights (Remodel)



Dedicated LED, Air-Loc® remodel housing with integral patented WarmDim®. LED color temperature warms while dimming to emulate the dimming performance of traditional incandescent light sources. Shallow housing allows for fit in 2 x 6 construction. IC remodel housing for remodel application where back side of ceiling is not accessible. Installs through an opening in the ceiling from below. Secured in place by factory installed remodel springs. Can be completely covered with insulation. When used with supplied ALG kit, stops infiltration and exfiltration of air, reducing heating and air cooling costs. LED housing is designed to provide 50,000 hours of life and is compatible with many standard Juno trims. 5 year limited warranty on LED components.

New Construction

14 1/2" L x 7 1/4" W x 5 1/2" H
Ceiling cutout: 6 3/4"

Example: IC22RLED WD G4 09LM 30K 90CRI 120 FRPC

Series	Dynamic Feature	Gen	Lumens	CCT	CRI	Voltage/Driver
IC22RLED 6" Remodel Housing	WD WarmDim®	G4N	06LM 600 Lumens	30K 3000K	90CRI	120 FRPC 120V Only; Forward Phase/ ELV Dimming
		G4	09LM 900 Lumens			

Accessories

Catalog No.	Description
LEDOPTIG3 MFL	Medium Flood Optic (50°)

¹ Not ENERGY STAR® certified.

ENERGY STAR® and T24 certification is dependent on trim finish. See housing spec sheet for specific information for each trim.

Juno 6" LED Downlight Trims

Open Trims



Conical

- 24 WWH White Baffle
- 24 BWH¹ Black Baffle
- 24 BSC¹ Black Baffle
- 24 BABZ¹ Black Baffle
- 24 BBL¹ Black Baffle

5 3/4" Aperture



Conical Cone

- 27 CWH Clear Alzak®
- 27 GWH Gold Alzak®
- 27 BWH Black Alzak®
- 27 PTSC Pewter Alzak®
- 27 WWH Gloss White
- 27 HZWH Haze
- 27 WHZWH Wheat Haze
- 27 WHZABZ Wheat Haze

5 3/4" Aperture



Octagonal 9024 WWH

5 3/4" Aperture



Luminous Disc (Frosted) 9324 SC

3 1/4" Aperture



Chrome Band 9524 SC

5 7/8" Aperture



Luminous Collar (Frosted) 9702

6 3/8" Aperture

Wall Wash Trims



Wall Wash

- 262G3 WWH White Baffle
- 262G3 BWH Black Baffle

Lensed Trims



Albalite

- 20 PW Shower/Closet Light
- 20 WH



Drop Opal

- 21 PW Shower/Closet Light
- 21 WH



Fresnel

- 22 WH



Frosted Lens*

- 239 WH



Frosted Lens with Clear Center

- 242 ABZ
- 242 SC
- 242 WH



Decorative Swirled Etched Opal Glass*

- 243 WH



White Baffle, Regressed Frosted Dome Lens*

- 2330W WH White
- 2330B WH Black



Beveled Frame, Frosted Dome Lens*

- 6101 ABZ
- 6101 SC
- 6101 WH

* Do not use reflector shipped with trim for LED housing. Discard or recycle reflector.