VuLite® 4" Line Voltage Housings and Trims

IC Housings

V4IC W

4" IC New Construction Energy efficient double wall housing. May be covered with insulation.



Dimensions: 12"L x 13-3/8"W x 6"H Ceiling Cutout: 4-1/2" Diameter

Accessories:

G2405 Set of (4) T-bar clips for installation in suspended ceilings.

TC Housings

V4TC W

4" TC New Construction Requires 3" spacing from insulation.

(Total 12-1/8"L x 13-3/8"W x 5-1/2"H Ceiling Cutout: 4-1/2" Diameter

V4TCR W

Dimensions:

4" TC Remodel Requires 3" spacing from insulation.

Dimensions:

12"L x 4-1/4"W x 5-1/2"H Ceiling Cutout: 4-3/8" Diameter



4" Compatible Trims - Line Voltage

Wet Location

Vet Locatio

Baffle V4034 WWH White V4034 BWH Black



Aperture: 3-7/8" Outer Diameter: 5"

Juno Compatible Housings: Lamp Wattage/Type V4IC W: 50W PAR20, 30W R20 V4TC W, V4TCRW: 50W PAR20, 50W R20

IC1P, TC1, TC1R: 50W PAR20, 50W R20 IC1: 50W PAR20, 30W R20

Cone V4017 CWH Clear



Aperture: 3-7/8" Outer Diameter: 5"

Juno Compatible Housings: Lamp Wattage/Type V4IC W, V4TC W, V4TCR W: 50W PAR20, 50W R20 IC1, IC1P, TC1, TC1R: 50W PAR20, 50W R20

Gimbal Ring V4010 WH White V4010 BN Brushed Nickel



Outer Diameter: 5"

Juno Compatible Housings: Lamp Wattage/Type V4IC W, V4TC W, V4TCR W: 50W PAR20 IC1P, TC1, TC1R: 50W PAR20

V4018 WH White

Eyeball



Outer Diameter: 5"

Juno Compatible Housings: Lamp Wattage/Type V4IC W, V4TC W, V4TCR W: 60W PAR16, 40W R16 IC1, IC1P, TC1, TC1R: 60W PAR16, 40W R16

Stippled Opal Lens Shower with Reflector V4012 WH White



Outer Diameter: 5"


Juno Compatible Housings: Lamp Wattage/Type

(Remove reflector when using Juno IC1 housing) V4IC W: 35W PAR20, 30W R20 V4TC W. V4TCR W: 50W PAR20, 50W R20

IC1: 35W PAR20, 30W R20 IC1P: 50W PAR20, 30W R20 TC1, TC1R: 50W PAR20, 50W R20

Gimbal Ring V4040 WH White V4040 BN Brushed Nickel

Outer Diameter: 5"



Juno Compatible Housings: Lamp Wattage/Type V4IC W: 35W MR16, 35 PAR16 120V Medium Base IC1, IC1P: 35W MR16, 35W PAR16 120V Medium Base