





Shown actual size: Diva preset dimmer and 1-gang Claro® wallplate in White (WH).

Product family features


- Large paddle switch with a captive linear-slide dimmer for a standard designer wallplate opening
- Preset dimmer
- Select lighter color models feature built-in soft-glow locator light
- **C•L™** dimmers offer more reliable dimming performance over standard dimmers when dimming CFLs and LEDs; they also provide full range dimming for incandescent and halogen bulbs as well as mixed loads types
- **C•L** dimmers feature HED™ Technology with advanced dimming circuitry designed for compatibility with most high-efficacy light bulbs
- **eco-dim®** model available
- 1000W preset dimmers have voltage compensation, which maintains stable light levels, despite line voltage variations
- Coordinating Claro®, Satin Colors® and Stainless Steel wallplates only available separately
- Custom engraving available for wallplates, see pg. 155


Control types

 Single-pole (one location)

 3-way or 4-way (two or more locations)


Direct load type compatibility

 Incandescent/halogen lighting

 Magnetic low-voltage lighting

 Electronic low-voltage lighting


 Fluorescent lighting

 LED lighting

 Dimmable CFL/LED lighting (screw-base)

 Ceiling fans

Load type requiring load interface

 Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage and capacity combinations.

For additional information, see pg. 174.

Available finishes

Use **BOLD** color code in model number (Example: DV-600P-**BR**)

Gloss finishes*



WH
White

LA
Light Almond

AL
Almond

IV
Ivory

GR
Gray

BR
Brown

BL
Black

Satin finishes*



SW
Snow

LS
Limestone

BI
Biscuit

ES
Eggshell

PD
Palladium

TP
Taupe

ST
Stone



BG
Bluestone

PL
Plum

SG
Sea Glass

TQ
Turquoise

GS
Goldstone

DS
Desert Stone

GB
Greenbriar



MS
Mocha Stone

TC
Terracotta

SI
Sienna

HT
Hot

MR
Merlot

MN
Midnight

SS
Stainless Steel

*Coordinating wallplates only available separately. For wallplate information, see pg. 160.

Stainless Steel wallplate includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) or Midnight (MN) controls.

Dimmers

Dimmers



- Paddle turns on/off
- Slide up to brighten; down to dim
- Locator light shines through paddle on select lighter colored models
- **C•L™** models provide more reliable dimming for screw-base CFL and LED lighting loads
- **eco-dim®** model guarantees at least 15% energy savings compared to a standard switch

Fan controls and switches

Fan controls



- Paddle turns on/off
- Slide up to increase speed; down to decrease speed
- Three quiet fan speeds for increased comfort
- For use with only one ceiling paddle fan
- Does not include locator light
- Designed to prevent motor hum

Switches



- Paddle turns on/off
- Use with any 15A load
- General purpose switching of all sources and motor loads
- Available with locator light

Dimmer model numbers



Incandescent/halogen dimmers

Dimmers

Single-pole	DV-600P- CC ³
120V 600W	DVSC-600P- CC ⁴
Single-pole	DV-10P- CC ³
120V 1000W	DVSC-10P- CC ⁴
3-way	DV-603P- CC ³
120V 600W	DVSC-603P- CC ⁴
3-way	DV-103P- CC ³
120V 1000W	DVSC-103P- CC ⁴
3-way/single-pole	DVCL-153P- CC ³
120V 600W	
3-way/single-pole	DVSCCL-153P- CC ⁴
120V 600W	

Refer to the “how to calculate wattage when mixing lamp types” table on, www.lutron.com/dimcflled, when using a combination of bulb types with the C•L™ dimmer.

eco-dim® dimmer with locator light

3-way/single-pole	DV-603PG- EE ²
120V 600W	

eco-dim model guarantees at least 15% energy savings compared to a standard switch.



Dimmable CFL bulbs (screw-base)



Dimmable LED bulbs (screw-base)

Dimmers

3-way/single-pole	DVCL-153P- CC ³
120V 150W	
3-way/single-pole	DVSCCL-153P- CC ⁴
120V 150W	

Refer to the “how to calculate wattage when mixing lamp types” table on, www.lutron.com/dimcflled, when using a combination of bulb types with the C•L dimmer.

Visit www.lutron.com for an approved list of dimmable CFL/LED bulbs.



Magnetic low-voltage dimmers

Dimmers

Single-pole	DVLV-600P- CC ³
120V 600 VA (450W)	DVSCLV-600P- CC ⁴
Single-pole	DVLV-10P- CC ³
120V 1000 VA (800W)	DVSCLV-10P- CC ⁴
3-way	DVLV-603P- CC ³
120V 600 VA (450W)	DVSCLV-603P- CC ⁴
3-way	DVLV-103P- CC ³
120V 1000 VA (800W)	DVSCLV-103P- CC ⁴

The stated VA (Volt-Ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (Watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

CC³: Gloss color codes, see pg. 87


CC⁴: Satin color codes, see pg. 87


EE²: Available in White (WH), Ivory (IV), Almond (AL) and Light Almond (LA)

(Wallplates not included with above, order separately, see pg. 160)


All models must be derated if ganged unless otherwise noted, see pg. 170.

Centurion® Controls pg. 42

Dimmers with
Rotate On/Off
Knob

Incandescent/
Halogen


C-600-
C-1000-

Incandescent/
Halogen



C-1500-
C-2000-


Rotary Dimmers
(Push On/Off)

Incandescent/
Halogen


C-600P-
C-10P-
C-603P-
C-103P-


Diva® Controls pg. 86


Dimmers with
Locator Light

Incandescent/
Halogen


DV-600P-
DVSC-600P-
DV-10P-
DVSC-10P-
DV-603P-
DVSC-603P-
DV-103P-
DVSC-103P-

Incandescent/
Halogen
eco-dim®
DV-603PG-

Tu-Wire®
Fluorescent

DVFTU-5A3P-
DVSCFTU-5A3P-

Electronic
Low-Voltage

DVELV-300P-
DVSCELV-300P-
DVELV-303P-
DVSCELV-303P-

Dimmable
CFL/LED
(screw-base)


DVCL-153PH-
DVCL-153P-
DVSCCL-153PH-
DVSCCL-153P-

Magnetic
Low-Voltage

DVLV-600P-
DVSCLV-600P-
DVLV-10P-
DVSCLV-10P-
DVLV-603P-
DVSCLV-603P-
DVLV-103P-
DVSCLV-103P-

3-Wire
Fluorescent
and Hi-lume®
LED Drivers

DVF-103P-
DVSCF-103P-
DVF-103P-277-
DVSCF-103P-277-

0-10V Fluorescent
and LED Drivers

DVTV-
DVSCTV-

Fan Controls



Quiet 3-Speed

DVFSQ-F-
DVSCFSQ-F-
DVFSQ-F-HO-