



ROOF JACKS & TIE WIRE

STANDARD-ROOF JACKS

PC 5230



Roof Jacks are applied to the roof to form a water-tight seal. They add additional support between the roof line and service entrance conduit or ventilation pipe.

FEATURES:

- 28 Gauge Steel
- Galvanized Steel
- Available in Stainless Copper

CAT. NO.	UPC	PIPE SIZE	BASE SIZE	STD	MSTR	WT/STD
RJ50	69600	1/2"	11" x 13"	12		24.08#
RJ75	69605	3/4"	11" x 13"	12		23.92#
RJ100	69610	1"	11" x 13"	12		23.06#
RJ125	69615	1-1/4"	11" x 13"	12		23.13#
RJ150	69620	1-1/2"	11" x 13"	12		22.87#
RJ200	69625	2"	11" x 13"	12		21.82#
RJ300	69630	3"	12-1/2" x 15"	12		15.22#
RJ400	69635	4"	12-1/2" x 15"	12		19.39#

3 IN 1 ROOF JACKS

PC 5250



Roof Jacks are applied to the roof to form a water-tight seal. They add additional support between the roof line and service entrance conduit or ventilation pipe.

FEATURES:

- 24 Gauge Steel
- Elastomer Collar

CAT. NO.	UPC	PIPE SIZE	BASE SIZE	STD	MSTR	WT/STD
RN3	10350	1/2", 3/4", 1" *	8-3/4", 12-1/2"	12		11.95#
RN4	10352	1-1/2", 2", 2-1/2", 3"	10-3/4" x 12-1/2"	12		18.82#

*Can be modified to fit 1-1/4" pipe, Fits any roof pitch - from flat to 45°
Tested for ultraviolet, ozone, and weather resistance.

STEEL/GALVANIZED-TIRE WIRE

PC 5030, 5035



Tie wire is used for many purposes, among them tying down PVC conduit in trenches before pouring concrete, as well as drop ceiling applications.

BLACK ANNEALED - PC 5030

CAT. NO.	UPC	STD	MSTR	WT/STD
TY164	28170	20		71.10#

GALVANIZED - PC 5035

CAT. NO.	UPC	STD	MSTR	WT/STD
VTYG	28180	20		68.35#

FEATURES:

- 16 1/2 Gauge
- 400 Ft. (3-1/2#)
- Black Annealed or Galvanized

TECH



TALK

**DOTTIE
PIPE
SUPPORT
#DPS**

**DUAL
CHANNEL
TECHNOLOGY**



See page C27 For More info

