

Switches with sensor



- Adjustable timeout — 1, 5, 15, or 30 minutes
- Occupancy/vacancy version can be easily programmed to work as vacancy (manual-on) sensor
- 180° field-of-view
- Uses standard single-pole and 3-way wiring
- Vacancy models meet California Title 24 Section 119(j) requirements
- 6 A (120/277 V) switch controls: incandescent, halogen, MLV, ELV, non-dim fluorescent (neutral required), and general purpose fans
- 2 A and 5 A switches control: incandescent, halogen, MLV, ELV, and non-dim fluorescent
- 5 A controls general purpose fans
- Works with up to nine companion switches
- See pg. 137 for more details

Switches

Switch with occupancy/vacancy sensor

Single-pole	MS-OPS2- XX ¹
120V 2A lighting	
Multi-location/3-way/ single-pole	MS-OPS5M- XX ¹
120V 5A lighting	
1/10HP @ 120V 3A fan	

Dual voltage switch with occupancy/vacancy sensor

Multi-location/3-way/ single-pole	MS-OPS6M2-DV- XX ¹
120V or 277V 6A lighting	
1/10HP @ 120V 3A fan	
Multi-location/3-way/ single-pole	MS-OPS6M2N-DV- XX ^{1*}
120V or 277V 6A lighting	
1/10HP @ 120V 3A fan	

Switch with vacancy sensor*

Single-pole	MS-VPS2- XX ¹
120V 2A lighting	
Multi-location/3-way/ single-pole	MS-VPS5M- XX ¹
120V 5A lighting	
1/10HP @ 120V 3A fan	

Dual voltage switch with vacancy sensor

Multi-location/3-way/ single-pole	MS-VPS6M2-DV- XX ¹
120V or 277V 6A lighting	
1/10HP @ 120V 3A fan	
Multi-location/3-way/ single-pole	MS-VPS6M2N-DV- XX ^{1*}
120V or 277V 6A lighting	
1/10HP @ 120V 3A fan	

XX¹: Gloss and Satin Colors® codes, see pg. 50
(Wallplates not included. Order separately, see pg. 169)

All models must be derated if ganged unless otherwise noted, see pg. 179.

***Requires neutral wire connection.**

****Minimum load required, see specification submittal.**

Sensors with switch



- Adjustable timeout — 1, 5, 15, or 30 minutes
- Occupancy/vacancy version can be easily programmed to work as vacancy (manual-on) sensor
- High-low sensitivity adjustment
- 6 A (120/277 V) switch controls incandescent, halogen, MLV, ELV, non-dim fluorescent, non-dim LED, and general purpose fans
- 2 A and 5 A switches control incandescent, halogen, MLV, ELV, non-dim LED and non-dim fluorescent; 5 A version also controls general purpose fans
- Works with up to nine companion switches; see pg. 58
- Works with a mechanical 3-way switch

Switches

Occupancy/vacancy sensor with switch

Single-pole	MS-OPS2- XX ¹
120 V 2 A lighting	
Multi-location/3-way/ single-pole	MS-OPS5M- XX ¹
120 V 5 A lighting	
1/10HP @ 120 V 3 A fan	

Occupancy/vacancy sensor with dual voltage switch

Multi-location/3-way/ single-pole	MS-OPS6M2-DV- XX ¹
120 V or 277 V 6 A lighting	
1/10HP @ 120 V 3 A fan	
Multi-location/3-way/ single-pole	MS-OPS6M2N-DV- XX ^{1*}
120 V or 277 V 6 A lighting	
1/10HP @ 120 V 3 A fan	

Vacancy sensor with switch
(CA Title 24 compliant)

Single-pole	MS-VPS2- XX ¹
120 V 2 A lighting	
Multi-location/3-way/ single-pole	MS-VPS5M- XX ¹
120 V 5 A lighting	
1/10HP @ 120 V 3 A fan	

Vacancy sensor with dual voltage switch
(CA Title 24 compliant)

Multi-location/3-way/ single-pole	MS-VPS6M2-DV- XX ¹
120 V or 277 V 6 A lighting	
1/10HP @ 120 V 3 A fan	
Multi-location/3-way/ single-pole	MS-VPS6M2N-DV- XX ^{1*}
120 V or 277 V 6 A lighting	
1/10HP @ 120 V 3 A fan	


All of the above do not need to be derated if ganged.

XX¹: Gloss and Satin Colors® codes, see pg. 138
(Wallplates not included, order separately, see pg. 169)


For more information on occupancy/vacancy sensors, visit www.lutron.com/occensors.
***Requires neutral wire connection.**

Maestro® Controls pg. 49


Digital Fade Dimmers




Incandescent/
Halogen
Dimmable CFL/
LED (screw-base)
C•L®
MACL-153M-




Incandescent/
Halogen
MA-600-
MSC-600M-
MA-1000-
MSC-1000M-




Incandescent/
Halogen
eco-dim®
MA-600G-




Electronic
Low-Voltage
MAELV-600-
MSCELV-600M-



Magnetic
Low-Voltage
MALV-600-
MALV-1000-
MSCLV-600M-
MSCLV-1000M-




3-Wire
Fluorescent
and Hi-lume®
LED Drivers
MAF-6AM-
MSCF-6AM-
MAF-6AM-277-
MSCF-6AM-277-




Incandescent/
Halogen
eco-minder®
MA-600I-


Switches and Timers



Digital Switch
for Lighting
or Fan
MA-S8AM-
MSC-S8AM-
MSCF-S6AM-277-
MAF-S6AM-277-




Countdown
Timer Switch
for Lighting
or Fan
(5–60 Minutes)
MA-T51-
MA-T51MN-




Countdown
eco-timer™
Switch for
Lighting or
Fan (5-30
Minute Limit)
MA-T530G-

Digital Fan Controls




Quiet 7-Speed
MA-FQ4FM-
MA-FQ3-




Preset
Fan/Light
Control

Incandescent/
Halogen
Dimmer
Quiet 7-Speed
MA-LFQHW-
MA-LFQM-




Fan canopy
module
CM-FQ1

Occupancy Sensing Dimmers



Incandescent/
Halogen with
Occupancy/
Vacancy or
Vacancy Sensor
MS-OP600M-
MS-VP600M-


Occupancy Sensing Switches



Switch with
Occupancy/
Vacancy or
Vacancy Sensor
MS-OPS2-
MS-VPS2-
MS-OPS5M-
MS-VPS5M-
MS-OPS6M2-DV-
MS-VPS6M2-DV-
MS-OPS6M2N-DV-
MS-VPS6M2N-DV-

Sensors pgs. 137-150


Maestro®
Occupancy
Sensing Dimmers



Incandescent/
Halogen Dimmer
with Occupancy/
Vacancy Sensors

MS-OP600M-
MS-VP600M-

Maestro
Occupancy
Sensing Switches



Switch with
Occupancy/
Vacancy or
Vacancy Sensors

MS-OPS2-
MS-VPS2-
MS-OPS5M-
MS-VPS5M-
MS-OPS6M2-DV-
MS-VPS6M2-DV-
MS-OPS6M2N-DV-
MS-VPS6M2N-DV-

Radio Powr Savr™



Radio Powr Savr™
Occupancy/
Vacancy or
Vacancy Sensors

LRF2-OCRB2-P-WH
LRF2-VCRB2-P-WH



Radio Powr Savr™
Occupancy/
Vacancy or
Vacancy Sensors

LRF2-OHLB-P-WH
LRF2-OKLB-P-WH
LRF2-OWLB-P-WH
LRF2-VHLB-P-WH
LRF2-VKLB-P-WH
LRF2-VWLB-P-WH




Radio Powr Savr
Daylight Sensor
LRF2-DCRB-WH

LOS
Wall Sensors



Passive Infrared
Heavy Duty

LOS-SIR-HD-WH



Passive Infrared
Two Circuit
Heavy Duty

LOS-S2IR-HD-WH